



Ubiquiti UACC-Intercom-SAM | Surface angle mount accessory | Intercom Surface Angle Mount



link to the product:

<https://www.batna24.com/gb/p/accessories-and-add-ons/ubiquiti-uacc-intercom-sam-surface-angle-mount-accessory-intercom-surface-angle-mount>

Price: **201.68 zł** gross / 163.97 zł net



Manufacturer: UBIQUITI

Referention number: DNXGHIKJKRMMHL



Product features

Product type	Mount
Height	324.8 mm
Width	113.7 mm
Depth	34.9 mm
Humidity measurement range	5 - 90%
Compatibility	UA-Intercom
Material	Polycarbonate (PC)
Operating temperature (T-T)	-30 - 60 °C
Brand compatibility	Ubiquiti
Product colour	Black
Mounting hardware type	Surface/Wall
Product weight	180 g

Full product description

Stable and precise mounting for UniFi Access intercoms

Ubiquiti UACC-Intercom-SAM is an **angled** mounting bracket that allows you to stably mount **your UniFi Access intercom** on various surfaces. Thanks to its robust construction and the use of UV-stabilized polycarbonate, it provides **weather resistance and long-lasting use**. If you are looking for a convenient and aesthetically pleasing intercom mounting solution, this product will meet your requirements.



Precise intercom angle adjustment

The **UACC-Intercom-SAM bracket** allows **the intercom to be mounted at an angle**, allowing for optimal field of view and better functionality. This allows you to precisely adjust the position of the device to suit your specific installation conditions.

Durable and rugged design

The product is made of **UV-stabilized polycarbonate with PU coating**, which ensures high resistance to UV radiation, changing temperatures and moisture. Robust materials ensure that the handle **does not deform and does not lose its properties** even with prolonged outdoor use. As a result, it can be used in various climatic conditions without risk of damage.



Adapted for installation on various surfaces

The **UACC-Intercom-SAM** mount is designed for **surface mounting**, making it fit on walls and other stable surfaces. This solution allows the UniFi Access intercom to be easily installed in an optimal location, without the need for additional adapters. This allows the user **to customize the installation according to individual needs**.

Wide operating temperature range

The mount is rated for a wide temperature range, **from -30°C to 60°C**, making it suitable for both frigid climates and hot conditions. In addition, **its humidity resistance of up to 90%** means that it can be installed outdoors without worrying about its durability. This guarantees reliable use in a variety of environments.

