



MikroTik cAP ac | Access point | RBcAPGi-5acD2nD, Dual Band, 2x RJ45 1000Mb/s



link to the product:

<https://www.batna24.com/gb/p/access-points/mikrotik-cap-ac-access-point-rbcapgi-5acd2nd-dual-band-2x-rj45-1000mb-s>

Price: **287.97 zł** gross / 234.12 zł net



Manufacturer: MIKROTIK

Referention number: DNXGFMKRJRMOK

Information:

MikroTik RBcAPGi 5acD2nD is a high-performance indoor Wi-Fi access point with an elegant design for wall or ceiling mounting. It offers dual-band 2.4 GHz and 5 GHz connectivity in the 802.11ac standard, providing 360° coverage. Equipped with RouterOS Level 4, two Ethernet PoE ports, and support for 802.3af/at PoE and passive PoE out, it makes network expansion easy. It also supports hardware IPsec acceleration and operates across a wide temperature range from -40°C to 50°C.

Product features

Regulatory Approvals	CE, FCC, IC, EAC, ROHS
Height	136 mm
Output voltage	57 V
Antenna type	Internal
LED indicators	Yes
Receiver sensitivity	2.4GHz: 1/11/6/54Mbps: -100/-94/-96/-78dBm @26/26/26/23dBm Tx; MCS0/7: -96/-73dBm @26/22dBm Tx 5GHz: 6/54Mbps: -96/-80dBm @26/21dBm Tx; MCS0/7/9: -96/-75/-70dBm @26/20/18dBm Tx
Width	136 mm
Depth	30 mm
Mounting kit	Yes
Maximum data transfer rate	867 Mb/s
Power consumption (max)	13 W
Harmonized System (HS) code	85176990
Networking standards	IEEE 802.11a
Ethernet LAN (RJ-45) ports	2

Antenna gain level (max)	2.5 gain
DC voltage range	17 V
Flash memory	16 MB
Operating temperature (T-T)	-40 - 50 °C
AC adapter included	Yes
Processor frequency	716 MHz
Operating system installed	RouterOS
Power over Ethernet (PoE)	Yes
Internal memory	128 MB
PoE adapter included	Yes
Placement	Ceiling
Processor model	IPQ4018
Built-in processor	Yes
Power over Ethernet (PoE) type supported	Active PoE
Antennas quantity	4
Antenna features	Integrated antenna
Product colour	White
Maximum data transfer rate (5 GHz)	867 Mb/s
Maximum data transfer rate (2.4 GHz)	300
Internal	No
5 GHz	Yes
2.4 GHz	Yes

Full product description

Mikrotik RBcAPGi 5acD2nD Access Point - wireless access point

Mikrotik RBcAPGi 5acD2nD CAP Capsman AC is a very efficient wireless AP access point for indoor applications. Its aesthetic and original design makes it look beautiful on both walls and ceilings. It has a two-band wireless radio connection, which supports two frequency bands: 2 GHz and 5 GHz, in 802.11ac and older. It provides a 360 degree range. The device is equipped with Mikrotik RouterOS Level 4 license operating system.



Extendability of the network

When the radio supports repeater mode, the two Ethernet ports give you the ability to expand your network with cables even if a PoE power supply is required, because cAP ac supports 802.3af/at PoE input on the first port and passive PoE output on the second port. The device also provides support for IPsec hardware acceleration.



The cAP ac frequency range

The MikroTik cAP ac (international) wireless access point supports the 2412-2484 MHz and 5150-5875 MHz bands. The specific frequency range may be limited by national regulations.



Main features:

- Operating temperature from -40°C to 50°C
- 2.4 GHz and 5 GHz wireless network
- Number of processor cores 4

