



MikroTik CRS326-24G-2S+IN | Switch | 24x RJ45 1000Mb/s, 2x SFP+



link to the product:

<https://www.batna24.com/gb/p/switches/mikrotik-crs326-24g-2sin-switch-24x-rj45-1000mb-s-2x-sfp>

Price: **717.05 zł** gross / 582.97 zł net



Manufacturer: MIKROTIK

Referention number: DNXGFPQODRMMMM

Product features

Regulatory Approvals	CE/RED, EAC, RoHS
Height	44 mm
Width	285 mm
Depth	144 mm
Input current	1.2 A
Rack mounting	Yes
Power consumption (max)	21 W
Rate limiting	Yes
Memory type	DDR3 SDRAM
Switch type	Managed
10G support	Yes
Flash memory	16 MB
DC input voltage	10 V
Operating temperature (T-T)	-40 to 60 °C
VLAN support	Yes
SFP+ module slots quantity	2
IP routing	Yes
Port mirroring	Yes
Ethernet LAN data rates	1000 Mb/s
Power supply included	Yes
Power over Ethernet (PoE)	Yes
Internal memory	512 MB

Power over Ethernet (PoE) voltage	30 V
Built-in processor	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Product colour	White
MAC address filtering	Yes
Number of power supply units	2
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	24

Full product description

MICROTIK CRS326-24G-2S+IN

MicroTik Cloud Router Switch **CRS326-24G-2S+IN** is a device based on **CSS326-24G-2S+RM** switch design. The main change is the introduction of dual boot option - the user can choose **RouterOS** or **SwitchOS**. The device has a **800 MHz** processor and **512 MB** RAM memory. **Mikrotik crs32624g2sin** is a device that will not let you down and will make your wireless networks work perfectly. Ask the question and we will answer it quickly. In our shop you will find pigtails, adapters, welders, cables and other fiber optic accessories, poe switches, poe adapters, poe power supplies, network cards, car cameras, ip cameras, monitoring kits, sfp modules (sfp inserts), media converters, access points, cpe client devices and others.



The most important features:

- 24 Gigabit Ethernet ports
- 2 SFP+ slots
- Dual boot - RouterOS or SwitchOS system
- Managing Layer2 and Layer3
- Built-in switch chip
- Power supply via passive PoE or DC plug, voltage: 9 - 30 V DC
- Desktop Enclosure



Specification CRS326-24G-2S+RM

The product is equipped with **24 Gigabit** ethernet ports and **2 SFP+ sloops**. **SFP** slots support both SFP and SFP+ inserts. **The SwOS** system allows management from the Web GUI, and features such as port isolation, port mirroring, ACL, RSTP lists, and **802.1Q VLAN** are available. The device can be powered via **passive PoE** or **DC** plug, the input voltage range is 9 - 30 V DC (24 V, 1.2 A power supply is included).