



MikroTik CRS326-24G-2S+RM | Switch | 24x RJ45 1000Mb/s, 2x SFP+



link to the product:

<https://www.batna24.com/gb/p/switches/mikrotik-crs326-24g-2srm-switch-24x-rj45-1000mb-s-2x-sfp>

Price: **727.58 zł** gross / 591.53 zł net



Manufacturer: MIKROTIK

Referention number: DNXFMJPOHRMMOQ



Product features

Height	44 mm
Width	440 mm
Depth	144 mm
Security algorithms	SNMP
Power consumption (max)	24 W
Console port	RJ-45
Harmonized System (HS) code	85176990
Networking standards	IEEE 802.1Q
Switch type	Managed
10G support	Yes
Flash memory	16 MB
Number of VLANs	4000
Spanning tree protocol	Yes
Broadcast storm control	Yes
Operating temperature (T-T)	-40 to 60 °C
AC adapter included	Yes
Rack mount kit	Yes
VLAN support	Yes
SFP+ module slots quantity	2
Processor frequency	800 MHz
Web-based management	Yes
Port mirroring	Yes

Power supply included	Yes
Internal memory	512 MB
Built-in processor	Yes
Product colour	Grey
Switch layer	L2+
Access Control List (ACL)	Yes
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	24
Operating system	RouterOS, SwitchOS

Full product description

MicroTik CRS326-24G-2S+RM

Mikrotik cloud router switch crs32624g2srm is a device based on CSS326-24G-2S+RM switch design. The main change is the introduction of the dual boot option - the user can choose the RouterOS or SwitchOS system himself. The device has 800 MHz processor and 512 MB RAM. Mikrotik crs32624g2srm is a device that will not let you down and will make your wireless networks work perfectly. Ask a question and we will answer it quickly. In our shop you will find pigtails, adapters, welders, cables and other fiber optic accessories, poe switches, poe adapters, poe power supplies, network cards, car cameras, ip cameras, monitoring kits, sfp modules (sfp inserts), media converters, access points, cpe client devices and others.



Features:

- 24 Gigabit Ethernet ports
- 2 SFP+ slots
- RouterOS or SwOS system
- management of Layer2 and Layer
- Power supply via passive PoE or DC plug, voltage: 9 - 30 V



Specification CRS326-24G-2S+RM

The product is equipped with 24 gigabit ethernet ports and 2 SFP+ sloops. SFP slots support both SFP and SFP+ inserts. SwOS system can be managed from the Web GUI and features such as port isolation, port mirroring, ACL, RSTP and 802.1Q VLAN. The device can be powered via passive PoE or DC plug, the input voltage range is 9 - 30 V DC (24 V, 1.2 A power supply is included).

CRS326-24G-2S+RM							
Mode	Configuration	1518 byte		512 byte		64 byte	
		kpps	Mbps	kpps	Mbps	kpps	Mbps
Switching	Non blocking Layer 2 throughput	3,576.1	43,427.8	10,338.3	42,345.9	65,476.2	33,523.8
Switching	Non blocking Layer 2 capacity	3,576.1	86,855.7	10,338.3	84,691.7	65,476.2	67,047.6
Switching	Non blocking Layer 1 throughput	3,576.1	44,000.0	10,338.3	44,000.0	65,476.2	44,000.0
Switching	Non blocking Layer 1 capacity	3,576.1	88,000.0	10,338.3	88,000.0	65,476.2	88,000.0