



MikroTik CSS326-24G-2S+RM | Switch | 24x RJ45 1000Mb/s, 2x SFP+



link to the product:

<https://www.batna24.com/gb/p/switches/mikrotik-css326-24g-2srm-switch-24x-rj45-1000mb-s-2x-sfp>

Price: **552.80 zł** gross / 449.43 zł net



Manufacturer: MIKROTIK

Referention number: DNFXFMHOLHRMMKN

Product features

Power source	DC/PoE
Height	44 mm
Width	440 mm
Depth	144 mm
Security algorithms	SNMP
Rack mounting	Yes
Mounting brackets included	Yes
Power consumption (typical)	19 W
Harmonized System (HS) code	85176990
Networking standards	IEEE 802.1Q
Switch type	Managed
10G support	Yes
IFU / User manual	Yes
Flash memory	2 MB
Number of VLANs	4000
Spanning tree protocol	Yes
Broadcast storm control	Yes
Operating temperature (T-T)	-40 to 70 °C
AC adapter included	Yes
VLAN support	Yes
Reset button	Yes
SFP+ module slots quantity	2

Web-based management	Yes
Port mirroring	Yes
Power supply included	Yes
Power over Ethernet (PoE)	Yes
Internal memory	2 MB
Power over Ethernet (PoE) voltage range	10 V
Built-in processor	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Product colour	White
Power connector	DC-in jack
Access Control List (ACL)	Yes
MAC address filtering	Yes
Number of power supply units	1
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	24

Full product description

MicroTik CSS326-24G-2S+RM

Cloud Smart Switch 326-24G-2S+RM is a SwOS-powered 24 port Gigabit Ethernet switch with two SFP+ ports in a 1U rackmount chassis that provides wired connectivity with several new switching functions. The device can be powered via passive PoE or DC plug, input voltage range is 12 - 30 V DC (21 V, 1.2 A power supply is included). In our shop you will also find: patch panels, poe adapters, poe switches, ip cameras, monitoring kits, network cards, sfp modules, access points, power strips, cpe client devices, media converters, extraction brackets, pigtails, fiber optic cables, wireless routers and other network devices. Ask questions if you need technical support.



Features:

- 24 gigabit ports of Eth
- 2 SFP+ slots
- Layer2 management
- SwOS system
- switch chip - Marvell 98DX3216A1
- Power supply via passive PoE or DC plug, input voltage: 12 - 30 V DC



Functions MikroTik CSS326-24G-2S+RM

The manageable MikroTik css32624g2srm (24x rj45 1000mbs 2x sfp+) switch provides all the basic functions of the managed switch, and more: it allows you to manage port-to-port forwarding, use MAC filter, configure VLANs, mirror traffic, apply bandwidth restrictions, and even customize some MAC and IP fields. The SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.

CSS326-24G-2S+RM							
Mode	Configuration	1518 byte		512 byte		64 byte	
		kpps	Mbps	kpps	Mbps	kpps	Mbps
Switching	Non blocking Layer 2 throughput	3,576.1	43,427.8	10,338.3	42,345.9	65,476.2	33,523.8
Switching	Non blocking Layer 2 capacity	3,576.1	86,855.7	10,338.3	84,691.7	65,476.2	67,047.6
Switching	Non blocking Layer 1 throughput	3,576.1	44,000.0	10,338.3	44,000.0	65,476.2	44,000.0
Switching	Non blocking Layer 1 capacity	3,576.1	88,000.0	10,338.3	88,000.0	65,476.2	88,000.0