



**MikroTik hAP ac lite tower |
WiFi Router |
RB952Ui-5ac2nD-TC, Dual
Band, 5x RJ45 100Mb/s**



link to the product:

<https://www.batna24.com/gb/p/routers/mikrotik-hap-ac-lite-tower-wifi-router-rb952ui-5ac2nd-tc-dual-band-5x-rj45-100mb-s>

Price: **196.90 zł** gross / 160.08 zł net



Manufacturer: MIKROTIK

Referention number: DNXFLPQKHRMMPM



Product features

Height	34 mm
LED indicators	Yes
Width	119 mm
Depth	98 mm
USB connector type	USB Type-A
Power consumption (max)	7 W
USB 2.0 ports quantity	1
Harmonized System (HS) code	85176990
Networking standards	IEEE 802.11a
Ethernet LAN (RJ-45) ports	5
Antenna gain level (max)	15 gain
Flash memory	16 MB
Power over Ethernet (PoE)	Yes
Placement	Table
AC input voltage	8 V
Product colour	Black
Internal	No
5 GHz	Yes
2.4 GHz	Yes

Full product description

Mikrotik Routerboard RB952Ui 5ac2nD TC hAP ac lite Tower Case

Routerboard RB952Ui 5ac2nD TC hAP ac lite Tower Case to **access point** capable of operating in dual-band mode, i.e. simultaneously in the 2.4 GHz and 5 GHz bands.



Well equipped routerboard

The device is equipped with 650 MHz processor, 64 MB RAM, five 10/100 Mbps Ethernet ports (PoE output on port #5), dual 2.4 GHz wireless network stream and one 5 GHz stream. Built-in USB port allows you to connect a 3G/ 4G modem. The hAP ac lite hardware runs on RouterOS software with level 4 license.



New universal housing and mounting kit

The universal Tower housing allows you to place the device in a horizontal or vertical position. A wall mounting kit is included with the product.



Operating frequency range

RB952UI-5AC2ND-TC (hAP ac lite Tower Case) operates in the 2412 - 2462 MHz and 5150 - 5835 MHz frequency ranges.



hAP ac lite (RB952Ui-5ac2nD)

