



MikroTik hAP | WiFi Router | RB951Ui-2nD, 2,4GHz, 5x RJ45 100Mb/s



link to the product:

<https://www.batna24.com/gb/p/routers/mikrotik-hap-wifi-router-rb951ui-2nd-24ghz-5x-rj45-100mb-s>

Price: **151.82 zł** gross / 123.43 zł net



Manufacturer: MIKROTIK

Referention number: DNxEEQQLFRMMKH

Information:

MikroTik RB951Ui-2nD hAP is a compact Wi-Fi access point and router ideal for home or small office use. It provides wireless Internet access in the 2.4 GHz band, as well as the option of a wired connection via Ethernet/LAN ports. The device runs on RouterOS level 4 and is preconfigured, making setup quick and easy. It can be powered via a jack socket or PoE, and the included power supply makes installation easier. The model offers a 650 MHz processor, 64 MB RAM, Passive PoE output on port 5, a USB port for 3G/4G modems, and wall-mounting capability.

Product features

Wireless standard	802.11b/g/n
Height	28 mm
LED indicators	Yes
Width	113 mm
Depth	89 mm
USB connector type	USB Type-A
Mounting kit	Yes
Power consumption (max)	5 W
USB 2.0 ports quantity	1
Harmonized System (HS) code	85176990
Ethernet LAN (RJ-45) ports	5
Antenna gain level (max)	1.5 gain
AC adapter included	Yes
Power over Ethernet (PoE)	Yes
Internal memory	64 MB
AC input voltage	6 V

Processor model	Qualcomm Atheros QCA9531-BL3A-R
Built-in processor	Yes
Antenna features	Integrated antenna
Product colour	White
Internal	Yes
2.4 GHz	Yes

Full product description

MicroTik RB951Ui 2nD hAP - access point and Wi-Fi router

RB951Ui 2nD hAP is a small **access point and Wi-Fi** router that is great for home or small office use, providing wireless Internet access. You can also use the Ethernet cable or LAN ports of the device to connect. The access point works on Mikrotik RouterOS level 4 operating system.



Wall-mountable

This compact device in an aesthetically pleasing casing will blend in perfectly with the surrounding decor. The Access point is also equipped with special brackets for wall mounting.



PoE Injector

RB951Ui-2nD access point can be powered via jack socket or PoE input via Ethernet cable. A power supply with a jack plug is included in the package. The hAP is pre-configured, so just plug in the Internet cable and power to start using the wireless network.



Main features:

- Wireless network in the 2.4 GHz frequency band
- 650 MHz processor
- 64 MB RAM
- Passive PoE output on port #5
- USB port to connect 3 G/ 4 G wireless modems

Ethernet test results

RB951Ui-2nD		QCA9531 (650Mhz) 100M all port test					
Mode	Configuration	1518 byte		512 byte		64 byte	
		kpps	Mbps	kpps	Mbps	kpps	Mbps
Bridging	none (fast path)	40.6	493.0	117.4	480.9	217.0	111.1
Bridging	25 bridge filter rules	40.6	493.0	70.1	287.1	70.9	36.3
Routing	none (fast path)	40.6	493.0	117.4	480.9	200.8	102.8
Routing	25 simple queues	40.6	493.0	79.6	326.0	90.8	46.5
Routing	25 ip filter rules	40.6	493.0	42.2	172.8	43.2	22.1