



MikroTik LtAP mini | LTE Router | RB912R-2nD-LTm, 2,4GHz 300Mb/s, 1x RJ45 100Mb/s, 1x miniPCI-e, dual SIM, GPS



4 752224 000637 >

link to the product:

<https://www.batna24.com/gb/p/lte-5g/mikrotik-ltap-mini-lte-router-rb912r-2nd-ltm-24ghz-300mb-s-1x-rj45-100mb-s-1x-minipci-e-dual-sim-gps>

Price: **332.67 zł** gross / 270.46 zł net



Manufacturer: MIKROTIK

Referention number: DNXGFMNSHRMMPL

Product features

Height	28.5 mm
WAN connection	Mobile network (SIM)
Width	139 mm
Depth	77 mm
USB connector type	Micro-USB
Maximum data transfer rate	54 Mb/s
Power consumption (max)	4 W
Harmonized System (HS) code	85176990
Networking standards	IEEE 802.11b
Ethernet LAN (RJ-45) ports	1
Antenna gain level (max)	1.5 gain
Flash memory	16 MB
Wi-Fi data rate (max)	54 Mbit/s
RS-232 interface	Yes
Operating temperature (T-T)	-40 - 70 °C
Operating system installed	RouterOS
Internal memory	64 MB
Placement	Table
AC input voltage	8 V
Built-in processor	Yes
Product colour	Black
Internal	No

5 GHz	No
2.4 GHz	Yes

Full product description

Wireless Access Point

LtAP mini is a small, weather-resistant wireless access point with integrated LTE antennas and a **miniPCI-e** socket, so you can use your own LTE modem.



Many power options

LtAP mini also has **one Ethernet LAN 10/100** port for wired devices. **The RS232** serial port provides access to the console for debugging. The device has several power options: **9-30V PoE input** via Ethernet port, DC and microUSB socket.



Rich features

LtAP mini has a special housing with a wall-mounting kit, two SIM sockets can switch between carriers and integrated **GPS** support, making it ideal for use in moving vehicles such as cars, buses and trains. Use the built-in GPS module to track the position of the vehicle in real time.

