



MikroTik Metal 52 ac | CPE | RBMetalG-52SHPack, 2,4GHz, 5GHz, 1x RJ45 1000Mb/s



link to the product:

<https://www.batna24.com/gb/p/radio-lines/mikrotik-metal-52-ac-cpe-rbmetalg-52shpack-24ghz-5ghz-1x-rj45-1000mb-s>

Price: **405.42 zł** gross / 329.61 zł net



Manufacturer: MIKROTIK

Referention number: DNXELPOOHRMNGQ



Product features

Height	215 mm
Output voltage	24 V
Receiver sensitivity	5GHz: -72, -93, -77, -91, -97 2.4GHz: -93, -78, -74, -69
Width	60 mm
Depth	38 mm
Mounting kit	Yes
High power	Yes
Maximum data transfer rate	54 Mb/s
Power consumption (max)	11 W
Package weight	778 g
Harmonized System (HS) code	85176990
Networking standards	IEEE 802.11a
Ethernet LAN (RJ-45) ports	1
Antenna gain level (max)	8 gain
Flash memory	16 MB
Wi-Fi data rate (max)	54 Mbit/s
Operating temperature (T-T)	-40 - 70 °C
AC adapter included	Yes
Output current	0.8 A
Operating system installed	RouterOS
Power over Ethernet (PoE)	Yes

Internal memory	64 MB
PoE adapter included	Yes
Placement	Pole
AC input voltage	10 V
Built-in processor	Yes
Antennas quantity	1
Antenna direction type	Omni-directional
Antenna features	Detachable antenna
Product colour	Metallic
Antenna connector type	N-type
Internal	No
5 GHz	Yes
2.4 GHz	Yes
Product weight	300 g

Full product description

MicroTik Metal 52 ac

Now with 802.11ac support, a Gigabit Ethernet port and a selectable 2.4 GHz or 5 GHz wireless band, a channel width of up to 80 MHz. The new Gigabit port will help you get the most out of your 802.11ac high-speed wireless network.



Weather-resistant housing

The device has a special metal casing ensuring resistance to difficult weather conditions. The metal 52 ac supports 2.4 GHz, 5 GHz and all previous wireless modes (802.11 b/g/n for 2.4 GHz and 802.11 a/n/ac for 5 GHz).



High transmission power

Transmission power is 1300 mW, integrated omnidirectional antennas have 6 (2.4 GHz) and 8 (5 GHz) dBi gain. Along with Metal 52 ac, other antennas can be used, adapted to individual requirements. It can work as client device, access point, or be used in point-to-point connections.



The most important features:

- The housing is resistant to various weather conditions
- Power 1300 mW
- 1x Gigabit Ethernet RJ-45
- wide channels - up to 80 MHz
- Supports 2.4 GHz, 5 GHz