



MikroTik SXTsq Lite2 | CPE |  
RBSXTsq2nD, 2,4GHz, 1x RJ45  
100Mb/s



link to the product:  
<https://www.batna24.com/gb/p/radio-lines/mikrotik-sxtsq-lite2-cpe-rbsxtsq2nd-24ghz-1x-rj45-100mb-s>

Price: **133.44 zł** gross / 108.49 zł net



Manufacturer: MIKROTIK  
Referention number: DNXXGMORHRMMPK

Product features

|                             |                    |
|-----------------------------|--------------------|
| Height                      | 34 mm              |
| WAN connection              | Ethernet (RJ-45)   |
| Width                       | 129 mm             |
| Depth                       | 129 mm             |
| Maximum data transfer rate  | 100 Mb/s           |
| Power consumption (max)     | 5 W                |
| Package weight              | 492 g              |
| Harmonized System (HS) code | 85176990           |
| Networking standards        | IEEE 802.11b       |
| Ethernet LAN (RJ-45) ports  | 1                  |
| Flash memory                | 16 MB              |
| Operating temperature (T-T) | -40 - 70 °C        |
| Package depth               | 180 mm             |
| Package height              | 45 mm              |
| Package width               | 255 mm             |
| Power over Ethernet (PoE)   | Yes                |
| Internal memory             | 64 MB              |
| AC input voltage            | 10 V               |
| Built-in processor          | Yes                |
| Antenna features            | Integrated antenna |
| Product colour              | White              |
| Internal                    | Yes                |
| 5 GHz                       | No                 |

|                |       |
|----------------|-------|
| 2.4 GHz        | Yes   |
| Product weight | 295 g |

## Full product description

### MicroTik SXTsq Lite2 Client device

SXTsq Lite2 is a compact and lightweight wireless outdoor device with a built-in antenna. Ideal for point-to-point connections or as a CPE unit. It is compact, weather-resistant, and easy to mount. It is designed to operate in the 2.4 GHz band, supports IEEE 802.11 b/g/n standard and uses 2x2 MIMO (dual-chain) technology. The maximum theoretical throughput is 300 Mbps.



### The SXTsq Lite2 antenna is twice as thin

The SXTsq Lite2 retains a 10 antenna and a 60° wide beam like the SXT Lite2, our previous model, but the design of the antenna has been improved and its size has been drastically reduced - the SXTsq is twice as thin.



### SXTsq Lite2 easy to install and configure

The housing has holes for direct fixing of the clamp in three different mounting locations, with the possibility of mounting on horizontal railings. The device has one 10/100 Mbit Ethernet port. There is also an easily accessible grounding that protects the device from lightning.



### The device and the set contains everything that is important:

- The device contains one 10 / 100Mbi Ethernet port
- Powered by passive PoE
- input voltage range is 10 - 30 V DC
- 24 V, 0.38 A and PoE injectors are included in the package



### The most important features:

- maximum transmission power 30 dBm
- integrated antenna with 10 dBi gain
- operation in the 2.4 GHz band
- Double polarity (dual-chain / 2x2 MIMO)
- Passive power supply via PoE
- Easy installation with the All-in-One housing
- LEDs indicating signal strength
- ESD protection up to 10kV ESD on the radio

### Wireless network specifications:

Wireless network

