



Orvaldi i1000LCD USB | UPS | 1000VA/600W, 2x 7Ah



link to the product:

<https://www.batna24.com/gb/p/ups/orvaldi-i1000lcd-usb-ups-1000va-600w-2x-7ah>

Price: **450.48 zł** gross / 366.24 zł net



Manufacturer: ORVALDI

Referention number: DNXXGGJHQFRMMGM



Product features

Height	208 mm
USB charging port	Yes
Width	135 mm
Depth	343 mm
UPS topology	Line-Interactive
Output power capacity	1 kVA
Battery capacity	24 Ah
Battery voltage	7 V
Input frequency	50 Hz
Display type	LCD
Number of batteries supported	2
Output power	600 W
Product colour	Black
Input operation voltage (max)	240 V
Input operation voltage (min)	220 V
Waveform	Pseudo sine
Product weight	10000 g

Full product description

ORVALDI i1000 LED USB

It is an advanced **UPS** unit **in line-interactive topology** based on **full microprocessor control**. **Additionally equipped with a USB charger**. Used with the latest technology and high efficiency to provide power to the protected loads both when **working with the network** and when **working from the battery**. Voltage shape is economical at the output of the UPS and is characterized by very quiet operation

during battery mode, which ensures the universality of application of this device to a wide range of switching power supplies (passive PFC) . In case of interruption of the supply voltage, it can immediately supply the energy stored in the batteries without any interruption. Switchover time to battery operation and vice versa is typically carried out within **2 to 6 ms**.

The ORVALDI i1000LCD USB model is an economical UPS for **home or small office up to a server or 2 computers**.



What are the characteristics of the ORVALDI I1000 LCD USB?

- "Green topology" saves 50% more energy than other UPSs in this class.
- Built-in intelligent charger provides 90% charge in as little as 5 hours.
- Superior microprocessor control ensures high reliability.
- Dual Boost and Buck AVR for voltage stabilization.
- Auto-restart when AC supply voltage returns.
- Simulated sine wave (approximate).
- Cold start function.
- Easy to read LCD display indicating UPS operating status.
- 5V charger on 2 USB ports on the front panel (max. 2.4 A).

•



