



Orvaldi V1100+ Sinus 2U LCD | UPS | 1100VA/990W, 2x 9Ah



link to the product:

<https://www.batna24.com/gb/p/ups/orvaldi-v1100-sinus-2u-lcd-ups-1100va-990w-2x-9ah>

Price: **1,882.15 zł** gross / 1,530.20 zł net



Manufacturer: ORVALDI

Referention number: DNXGGJHNKRMMIN

Product features

Height	88 mm
LED indicators	Yes
Response time	10 ms
USB charging port	Yes
Serial interface	Yes
Width	438 mm
Depth	410 mm
Audible alarm(s)	Yes
UPS topology	Line-Interactive
Emergency Power Off (EPO)	Yes
Output power capacity	1.1 kVA
ECO mode	Yes
Battery capacity	9 Ah
Battery voltage	12 V
Humidity measurement range	0 - 90%
Input frequency	50 Hz
Serial ports quantity	1
Performance	89 %
Operating temperature (T-T)	0 - 40 °C
Rack capacity	2U
Power protection features	Overcharge
Cold start	Yes

Noise level	55 decibel
Audible alarm modes	Alarm when on battery
Display type	LCD
Serial interface type	RS-232
Number of batteries supported	2
Output power	990 W
AC outlet types	IEC 320
Product colour	Black
Output voltage Total Harmonic Distortion (THD)	10 %
Crest factor	3:1
Power factor	0.9
Efficiency (ECO mode)	97 %
Automatic Voltage Regulation (AVR)	Yes
Output voltage regulation	25 %
Output frequency	50 Hz
Output operation voltage (max)	240 V
Output operation voltage (min)	220 V
Input operation voltage (max)	290 V
Input operation voltage (min)	162 V
Waveform	Sine
Product weight	13400 g

Full product description

Orvaldi V1100 Sinus 2U LCD

Uninterruptible power supplies of the UPS type provide short-term operation of home or office equipment in the event of a power cut in the general network. Operating in normal mode, UPSs, thanks to their built-in AVR, act as a voltage stabilizer. The voltage range of the mains supply is 162 to 290V. **ORVALDI V(L) 1.1kVA to 3kVA** with a power factor of 0.9, provides servers with full power protection from power failures as well as from the effects of power surges and peaks.



With the added advantage of a universal Rack / Tower chassis and an easy-to-read and user-friendly LCD, **the Orvaldi V1100 Sinus 2U LCD** is ideal for networking, telecommunications, servers and critical applications.



Characteristics

- Pure sinusoidal output voltage
- Output power factor 0.9

- User-friendly and easy-to-use LCDs
- Rack / Tower design
- Line interactive topology
- Built-in AVR voltage regulation circuit
- Programmable power management outputs
- ECO operation for energy saving (performance correcting Optimizer)
- Emergency power off (EPO) function
- USB/RS-232 communication available
- Optional SNMP card and AS400 relay card

