



Orvaldi V2000 on-line 2U LCD | UPS | 2000VA/1600W, 4x 9Ah



link to the product:

<https://www.batna24.com/gb/p/ups/orvaldi-v2000-on-line-2u-lcd-ups-2000va-1600w-4x-9ah>

Price: **3,002.70 zł** gross / 2,441.22 zł net



Manufacturer: ORVALDI

Referention number: DNXGGJHNRMLPQ

Product features

Height	88 mm
LED indicators	Yes
Response time	0 ms
Battery recharge time	4 h
Serial interface	Yes
Width	438 mm
Depth	380 mm
Audible alarm(s)	Yes
UPS topology	Double-conversion (Online)
Emergency Power Off (EPO)	Yes
Output power capacity	2 kVA
ECO mode	Yes
Battery capacity	7 Ah
Battery voltage	12 V
Humidity measurement range	20 - 90%
Input frequency	45 Hz
Serial ports quantity	1
Performance	88 %
Operating temperature (T-T)	0 - 40 °C
Rack capacity	2U
Cold start	Yes
Noise level	55 decibel

Audible alarm modes	Alarm when on battery
Display type	LCD
Serial interface type	RS-232
Charging current	1 A
Number of batteries supported	2
Output power	1600 W
Product colour	Black
Output voltage Total Harmonic Distortion (THD)	2 %
Crest factor	3:1
Output power factor	0.8
Input power factor	0.99
Efficiency (On-line mode)	85
Output frequency	50 Hz
Output operation voltage (max)	240 V
Output operation voltage (min)	208 V
Input operation voltage (max)	300 V
Input operation voltage (min)	110 V
Waveform	Sine
Product weight	13200 g

Full product description

ORVALDI V2000 on-line 2U LCD UPS (2000VA/1600W)

Most commonly used for **protection for your servers and critical loads** such as medical devices. The double conversion design can **guarantee reliable and stable protection** for all sensitive devices. It does not use energy that has been stored in batteries - it gives **pure stabilized sine wave output (230V +/- 1%)**. The device adopts **wider allowable input voltage** under harsh conditions.



What are the characteristics of the ORVALDI V2000 UPS?

- Double voltage conversion (on-line, no switching)
- Power Factor 0.8
- Wide input voltage range (110-300V AC)
- Universal rack/tower design
- ECO operation mode
- Input power factor correction 0.99
- Programmable power management outputs

- USB/RS communication available
- SNMP card, AS400 relay card

•

