



**Orvaldi V3000 on-line 2U LCD
| UPS | 3000VA/2400W, 6x
9Ah**



link to the product:

<https://www.batna24.com/gb/p/ups/orvaldi-v3000-on-line-2u-lcd-ups-3000va-2400w-6x-9ah>

Price: **3,536.30 zł** gross / 2,875.04 zł net



Manufacturer: ORVALDI

Referention number: DNXGGJHNIRMMGP

Product features

Height	88 mm
Response time	0 ms
Battery recharge time	4 h
Width	438 mm
Depth	600 mm
Output power capacity	3 kVA
Battery capacity	9 Ah
Battery voltage	12 V
Input frequency	45 Hz
Performance	88 %
Noise level	55 decibel
Charging current	1 A
Output power	2700 W
Output voltage Total Harmonic Distortion (THD)	2 %
Output frequency	50 Hz
Output operation voltage (max)	240 V
Output operation voltage (min)	208 V
Input operation voltage (max)	300 V
Input operation voltage (min)	110 V
Product weight	14800 g

Full product description

ORVALDI V2000 on-line 2U LCD UPS (2000VA/1600W)

Most commonly used for **protection for your servers and critical loads such as medical** devices. The double conversion design can guarantee reliable and stable protection for all sensitive devices. It does not use energy that has been stored in batteries - it gives **pure stabilized sine wave output (230V +/- 1%)**. The device adopts wider allowable input voltage under harsh conditions.



What are the characteristics of the ORVALDI V3000 UPS?

- Double voltage conversion (on-line, no switching)
- Power Factor **0.9**
- Wide input voltage range (**110-300V AC**)
- Universal rack/tower design
- ECO Mode of operation
- 6 "computer" output sockets **IEC320 C13 10A** and one **IEC320 C19 16A**
- Input power factor correction **0.99**
- Programmable power management outputs
- Emergency power off function
- **USB/RS-232** communication available
- SNMP card, AS400 relay card

