



Orvaldi VT1K on-line Tower | UPS | 1000VA/900W, 2x 9Ah



link to the product:

<https://www.batna24.com/gb/p/ups/orvaldi-vt1k-on-line-tower-ups-1000va-900w-2x-9ah>

Price: **1,029.26 zł** gross / 836.80 zł net



Manufacturer: ORVALDI

Referention number: DNXGGJHMKRMMHP

Product features

Height	220 mm
USB charging port	Yes
Width	145 mm
Depth	282 mm
Audible alarm(s)	Yes
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Typical backup time at full load	5 min
Battery capacity	9 Ah
Battery voltage	12 V
Input frequency	40 Hz
Cold start	Yes
Audible alarm modes	Alarm when on battery
Serial interface type	RS-232
Number of batteries supported	2
Output power	900 W
Product colour	Black
Crest factor	3:1
Output operation voltage (max)	240 V
Output operation voltage (min)	200 V
Input operation voltage (max)	280 V
Input operation voltage (min)	120 V

Waveform	Pure sine
Product weight	9800 g

Full product description

ORVALDI VT1K on-line Tower

This model is ideal for **servers, critical workstations and highly critical devices (used in the medical field)**.



The **Orvaldi VT1K on-line Tower** is equipped with the double conversion of the Orvaldi VT on-line power supply series, which guarantees reliable and stable protection for your sensitive devices. It can accept a wider allowable input voltage for harsh environments without using the energy stored in the batteries. It offers us **pure stabilized sine wave output (230V /- 1%)**. This is protection for your servers and critical loads such as medical devices that will never fail.

What are the characteristics of the ORVALDI VT1K ON-LINE TOWER?

- Features dual voltage conversion (no switching, on-line)
- Equipped with an output power factor of 0.9
- Wide input voltage range (110-300V AC)

- User friendly and easy to use
- ECO Mode
- USB/RS-232 communication available
- Additional: SNMP card and AS400 relay card