



Orvaldi VT3K on-line Tower | UPS | 3000VA/2700W, 6x 9Ah



link to the product:

<https://www.batna24.com/gb/p/ups/orvaldi-vt3k-on-line-tower-ups-3000va-2700w-6x-9ah>

Price: **2,928.78 zł** gross / 2,381.12 zł net



Manufacturer: ORVALDI

Referention number: DNXXGJHMMRMMJN

Product features

Height	318 mm
Width	190 mm
Depth	421 mm
Audible alarm(s)	Yes
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Battery capacity	9 Ah
Battery voltage	72 V
Input frequency	40 Hz
Auto-restart	Yes
Noise level	55 decibel
Audible alarm modes	Alarm when on battery
Display type	LCD
Number of batteries supported	6
Output power	2700 W
AC outlet types	IEC 320
Product colour	Black
Power factor	0.9
Automatic Voltage Regulation (AVR)	Yes
Output operation voltage (max)	240 V
Output operation voltage (min)	200 V
Input operation voltage (max)	240 V

Input operation voltage (min)	220 V
Waveform	Pure sine
Product weight	27.6 g

Full product description

ORVALDI VT3K on-line Tower

This model is ideal for **servers, critical workstations and highly critical devices (used in medicine)**. It has three times the power of its [first predecessor](#).



The **Orvaldi VT3K on-line Tower** is equipped with the double conversion of the Orvaldi VT on-line power supply series, which guarantees reliable and stable protection for your sensitive devices. It can accept a wider allowable input voltage for harsh environments without using the energy stored in the batteries. It offers us **pure stabilized sine wave output (230V +/- 1%)**. This is protection for your servers and critical loads such as medical devices that will never fail.

What are the characteristics of the ORVALDI VT3K ON-LINE TOWER?

- Features dual voltage conversion (no switching, on-line)
- Equipped with an output power factor of 0.9
- Wide input voltage range (110-300V AC)
- User friendly and easy to use
- ECO Mode
- USB/RS-232 communication available
- Additional: SNMP card and AS400 relay card