



Extralink SFP 1.25G | SFP Module | 1,25Gbps, LC/UPC, 1550nm, 80km, single mode, DOM



5 902560 368024 >

link to the product:

<https://www.batna24.com/gb/p/sfp-modules/extralink-sfp-125g-sfp-module-125gbps-lc-upc-1550nm-80km-single-mode-dom>

Price: **84.01 zł** gross / 68.30 zł net

Manufacturer: EXTRALINK



Referention number: DNXFLIKHRMMHM

Product features

Regulatory Approvals	FCC
SFP transceiver type	Fiber optic
CD-ROM interface type	SFP
Storage temperature (T-T)	-40 - 85 °C
Compliance certificates	CE
Maximum data transfer rate	1250 Mb/s
Humidity measurement range	5 - 85%
Operating temperature (T-T)	0 - 70 °C
Single-mode fiber (SMF) supported	Yes
Wavelength	1550 nm
Maximum transfer distance	80000 m
Rx wavelength (max)	1580 nm
Rx wavelength (min)	1260 nm
Tx wavelength (max)	1580 nm
Tx wavelength (min)	1480 nm
Maximum spike current	0.3 A

Full product description

High-performance Extralink SFP 1.25G 1550NM 80KM SM DDM LC DX module

The **Extralink SFP 1.25G 1550NM module** is a high-performance, cost-effective **SFP optical insert** that supports data transmission at **1.25 Gbps**, with a range of **up to 80 km** using SMF. The single-mode SFP module is equipped with a PIN photodetector and a DFB laser using **1550 nm** wavelengths. The Extralink SFP 1.25G 1550NM has an **LC duplex output connector**, and is compliant with SFP MSA and SFF-8472 standards and RoHS directive.



Special features