



Teltonika TSW010 | Switch | 5x RJ45 100Mb/s, Passive PoE, IP30, DIN



link to the product:

<https://www.batna24.com/gb/p/switches/teltonika-tsw010-switch-5x-rj45-100mb-s-passive-poe-ip30-din>

Price: **97.92 zł** gross / 79.61 zł net



Manufacturer: TELTONIKA

Referention number: DNXXGKKSFRRMMKP



Product features

Regulatory Approvals	CE, REACH, RoHS, WEEE UKCA, FCC, IC, CB, RCM
Power source	DC/PoE
Height	27.4 mm
Input voltage	9 V
LED indicators	Yes
Width	113.1 mm
Depth	80.5 mm
Packet buffer memory	0.128 MB
Power consumption (max)	0.9 W
Power consumption (typical)	0.3 W
Humidity measurement range	10 - 90%
DIN rail mounting	Yes
Switching capacity	1 Gb/s
Networking standards	IEEE 802.3
10G support	No
Auto MDI/MDI-X	Yes
Operating temperature (T-T)	-40 to 75 °C
Jumbo frames	2048
Jumbo frames support	Yes
MAC address table	2000 entries
International Protection (IP) code	IP30

Power over Ethernet (PoE) ports quantity	1
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Product colour	Black
Power connector	DC-in jack
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Watch case material	Aluminium
Basic switching RJ-45 Ethernet ports quantity	5
Product weight	146.5 g

Full product description

Affordable switch for industrial applications

Need a simple, easy-to-use switch without the hassle of installation or configuration? There's no need to look any further. The **Teltonika TSW010** is designed as a **plug-n-play switch**, meaning it doesn't require a specially trained engineer to manually configure, monitor or manage. The front-facing ports and built-in DIN-rail mount are additional points that eliminate the need for additional mounting kits and ensure the smoothest possible installation of the device, even in the most complex environments.



Key features of Teltonika TSW010

- Plug-n-Play without additional configuration
- Industrial design, anodized aluminum housing
- Integrated DIN rail mount and surface mount options
- Wide range of supported supply voltages
- 5 Ethernet ports with speeds up to 100 Mbps
- Wide operating temperature range

100Mbps Ethernet ports

Teltonika's **TSW010 switch** is designed for **machine-to-machine (M2M)** communications, where high data rates are not required. A **data rate of 100 Mbps is often more than sufficient**, for example, in monitoring, control and management applications where large amounts of data are not transmitted. Therefore, with **five 10/100 Ethernet ports**, the TSW010 can equip your solution with network connectivity and speeds that are ideal for most industrial solutions. These ports are an important reason why this device is one of the most cost-effective on the market, ensuring that you don't overpay for features you won't need.



Switch for professional applications

Its wide range of supported supply voltages (9-30V) and robust design make it suitable for professional solutions.



Thoughtful design and ease of installation

The compact size and integrated DIN-rail mount allow for easy installation in a variety of industrial environments.

