



Teltonika TSW200 | PoE+ Switch | 8x RJ45 1000Mb/s PoE+, 2x SFP, 240W



link to the product:

<https://www.batna24.com/gb/p/switches/teltonika-tsw200-poe-switch-8x-rj45-1000mb-s-poe-2x-sfp-240w>

Price: **365.75 zł** gross / 297.36 zł net



Manufacturer: TELTONIKA

Referention number: DNXXGGJKOKRMMLM

Product features

Power source	mains electricity
Height	132 mm
LED indicators	LAN
Wall mountable	Yes
Width	95.1 mm
Depth	44.2 mm
Packet buffer memory	0.128 MB
Rack mounting	Yes
Power consumption (max)	106 W
Power consumption (typical)	1.8 W
DIN rail mounting	Yes
Networking standards	IEEE 802.3
Switch type	Unmanaged
Auto MDI/MDI-X	Yes
DC input voltage	7 V
Operating temperature (T-T)	-40 to 75 °C
Total Power over Ethernet (PoE) budget	240 W
Jumbo frames	9216
Jumbo frames support	Yes
MAC address table	2000 entries
International Protection (IP) code	IP30
Power supply included	No

Power over Ethernet (PoE) ports quantity	8
Power over Ethernet (PoE)	Yes
SFP module slots quantity	2
Power over Ethernet (PoE) power per port	30 W
Power over Ethernet (PoE) voltage	57 V
Product colour	Aluminium
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Watch case material	Aluminium
Basic switching RJ-45 Ethernet ports quantity	8
Product weight	456 g

Full product description

TSW200 industrial unmanaged switch from Teltonika Networks

The **TSW200** is the first switch in the Teltonika Networks portfolio with **eight Gigabit Ethernet ports supporting IEEE802.3af and IEEE802.3at Power-over-Ethernet standards**. Now you can connect more devices and power them simultaneously with a **power budget of 240W**. This unmanaged switch requires no configuration, so the time and resources required to install the solution are minimal. The plug-and-play design of this switch will allow you to connect multiple IP cameras, point-of-sale (POS) systems, access points or other PoE-compatible devices to the Internet in minutes and reduce unnecessary cabling.



Key features of Teltonika TSW200

- 2 SFP ports for long-range fiber optic communications
- 8 PoE ports with support for 802.3af and 802.3at standards
- 8 Gigabit Ethernet ports with speeds up to 1000 Mbps
- Industrial design and durable aluminum housing
- Total PSE power budget up to 240 watts
- Plug-n-Play - No configuration required
- DIN rail and surface mounting options



Gigabit ports with PoE and SFP ports

This unmanaged switch has **8 Gigabit Ethernet ports** supporting **IEEE802.3af and IEEE802.3at PoE** standards , with which it powers other devices in your solution. The TSW200 is also equipped with **2 SFP ports** for long-range fiber communication.



Easy installation and durable housing

The **Teltonika TSW200 features a rugged and durable design** to withstand adverse conditions and harsh temperature ranges. It comes with **wall and DIN rail mounting options** for easy installation. So this switch will fit virtually any corporate, commercial or industrial scenario

with broadband, remote applications that require reliable data and power connectivity.

