



Totolink EX1200T | WiFi Extender | AC1200, Dual Band, 1x RJ45 100Mb/s, 2x 5dBi



link to the product:

<https://www.batna24.com/gb/p/wi-fi-signal-boosters/totolink-ex1200t-wifi-extender-ac1200-dual-band-1x-rj45-100mb-s-2x-5dbi>

Price: **114.99 zł** gross / 93.49 zł net

Manufacturer: TOTOLINK



The Smartest Network Device

Referention number: DNXXGFPHQMRMPQ

Product features

Storage relative humidity (H-H)	5 - 95%
Height	66 mm
Antenna type	External
LED indicators	LAN
Width	117 mm
Depth	72 mm
Input current	0.1 A
Storage temperature (T-T)	-40 - 70 °C
Humidity measurement range	5 - 95%
Data transfer rate	1167 Mb/s
Networking standards	IEEE 802.11a
Ethernet LAN (RJ-45) ports	1
Antenna gain level (max)	5 gain
IFU / User manual	Yes
SSID Broadcast	Yes
Wi-Fi data rate (max)	1167 Mbit/s
Plug and Play	Yes
Operating temperature (T-T)	0 - 50 °C
Cabling technology	10/100Base-T(X)
Quality of Service (QoS) support	Yes
Package type	Box
Reset button	Yes

Firmware upgradeable	Yes
Web-based management	Yes
WPS push button	Yes
Power over Ethernet (PoE)	No
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Wi-Fi standards	802.11a
Wi-Fi	Yes
AC input frequency	50 Hz
AC input voltage	100 V
Antennas quantity	2
RJ-45 ports quantity (transmitter)	1
Product colour	Black
Host interface	RJ-45
Maximum transfer distance	40 m
DHCP client	Yes
DHCP server	Yes
Watch case material	Acrylonitrile butadiene styrene (ABS)
Type	Network transmitter & receiver

Full product description

EX1200T - dual-band AC1200 Wi-Fi amplifier

- Compliant with IEEE 802.11a / b / g / n / ac.
2. Turn your single-band Wi-Fi into dual-band Wi-Fi.
 3. Maximum transmission speed up to **1167 Mbps (5G: 867 Mbps, 2.4G: 300 Mbps)**
 4. 2 external 5dBi antennas for good range
 5. Supports quick and easy configuration with a smartphone.
 6. Operation of quick wavelength extension with WPS button
 7. Intelligent LED light visually shows the connection status
 8. Support for 2 operating modes: AP and Repeater.
 9. Compact design saves space.



Wireless dual-frequency speed

The **EX1200T** range amplifier **is compatible with 802.11ac wireless standard**, allowing transmission of signals up to **1167 Mbps** (AC1200) on both bands at the same time.



Determine the optimal installation location

The LED system in the EX1200T provides information on the strength of the signal received from the source, to help users easily identify and install the device in an optimal location. Equipped with an all-in-one socket-compatible holder and compact size, users can now install the device anywhere in their home without having to worry about taking up much space.