



TP-Link LS108G | Switch | 8x RJ45 1000Mb/s



link to the product:

<https://www.batna24.com/gb/p/switches/tp-link-ls108g-switch-8x-rj45-1000mb-s>

Price: **82.47 zł** gross / 67.05 zł net



Manufacturer: TP-LINK

Referention number: DNXGFQPLERMMKQ

Product features

Regulatory Approvals	CE, FCC, RoHS
Storage relative humidity (H-H)	5 - 90%
Power source	mains electricity
Height	25 mm
Input voltage	5 V
LED indicators	Activity
Width	158 mm
Depth	99 mm
Auto-negotiation	Yes
Packet buffer memory	1.5 MB
Input current	0.6 A
Storage temperature (T-T)	-40 to 70 °C
Rack mounting	No
Power consumption (max)	3.7 W
Package weight	470 g
Humidity measurement range	10 - 90%
Harmonized System (HS) code	85176990
Switching capacity	16 Gb/s
Quick start guide	Yes
Networking standards	IEEE 802.1p
Switch type	Unmanaged
10G support	No
Auto MDI/MDI-X	Yes

Operating temperature (T-T)	0 – 40 °C
Package depth	191 mm
Package height	92 mm
Heat dissipation	12.617 British thermal unit per hour
Package width	130 mm
Quality of Service (QoS) support	Yes
Flow control support	Yes
Jumbo frames	16000
Jumbo frames support	Yes
MAC address table	4000 entries
Power supply included	Yes
Power over Ethernet (PoE)	No
Gigabit Ethernet (copper) ports quantity	8
Product colour	Blue
Power connector	DC-in jack
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	8


Full product description

Desktop Switch, 8 ports 10/100/1000Mbps

The TP-Link LS108G is a **LiteWave** Series switch that is a great choice for anyone looking for an easy and affordable solution to expand an existing wired network. This switch features simple operation and high reliability. Thanks to **plug and play** installation, the network can be expanded with other devices very quickly. The device offers a total of 8 **10/100/1000 Mbps** RJ45 ports with auto adaptation supporting AUTO-MDI / MDIX.

Main advantages

- 8 x 10/100/1000Mb RJ45 with auto adaptation with Auto-MDI / MDIX support.
- Green Ethernet technology to save power consumption.
- IEEE 802.3x flow control ensures reliable data transmission.
- Plug and play, no configuration required
- Fanless design for quiet operation.
- 802.1p / DSCP QoS support.



Plug and Play installation

Thanks to the **Plug and Play** functionality, the switch only needs to be connected to the power supply, and the installation and configuration of the device will run automatically.




Durable metal housing

The outer casing of the LS108 Switch is made of high-grade steel, which ensures a long service life of the device. It also passes a series of rigorous reliability tests. The small size of the LS108G makes it ideal for installation at home or small businesses.



Use where and how you want

The LS108G easily communicates with network devices such as; **computers, printers, webcams or IPTV**. So it's ideal for dormitory, home, small business and surveillance applications.



Akademik



Obiekt monitorowany



Dom



Mała firma