



TP-Link TL-SF1016 | Switch | 16x RJ45 100Mb/s, Rack



link to the product:

<https://www.batna24.com/gb/p/switches/tp-link-tl-sf1016-switch-16x-rj45-100mb-s-rack>

Price: **193.84 zł** gross / 157.59 zł net



Manufacturer: TP-LINK

Referention number: DNXIJNILOHSPP

Product features

Storage relative humidity (H-H)	5 - 90 %
Height	44 mm
LED indicators	Yes
Width	440 mm
Depth	180 mm
Packet buffer memory	2 MB
Storage temperature (T-T)	-40 to 70 °C
Cables included	AC
Rack mounting	Yes
Power consumption (max)	2.23 W
Humidity measurement range	10 - 90%
Harmonized System (HS) code	85176990
Switching capacity	3.2 Gb/s
Networking standards	IEEE 802.3i
Switch type	Unmanaged
10G support	No
Auto MDI/MDI-X	Yes
Operating temperature (T-T)	0 - 40 °C
Rack mount kit	Yes
MAC address table	8000 entries
Power over Ethernet (PoE)	No
AC input frequency	50 Hz

AC input voltage	100 V
Copper ethernet cabling technology	100BASE-TX
Product colour	Black
Power connector	DC-in jack
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Basic switching RJ-45 Ethernet ports quantity	16

Full product description

Network switch for rack mounting

TP-Link TL-SF1016 is a **network switch** with an attractive price, secure internal power supply and rack-mounting capability to make it the best solution for networks with up to 16 users. The device is equipped with 16 **Fast Ethernet** ports and operates on the basis of innovative technologies allowing to save up to 40% of energy.



High performance

The **TL-SF1016** switch is a good choice for network administrators looking for the best and efficient solutions at the lowest possible prices. The smooth traffic switching architecture allows packets to be transferred and filtered at full speed with maximum bandwidth. 10K jumbo frames increase the efficiency of transferring large amounts of data. **TL-SF1016** is designed for demanding users, for whom high quality of network connections is a priority.



Advanced features

Automatic switch operation with plug and play ensures simple and trouble-free installation. No additional software is required. Thanks to the MDI/MDIX function there is no need for crossover cables or uplink ports. The automatic connection negotiation function detects the speed of the connected device (10 or 100 Mbps) on each port for best performance. The desktop enclosure allows to place the device in places where there is not much free space. It is also safe and convenient to place the switch in a rack. LEDs indicate the operating status of the device and detect major transmission errors.

