



TP-Link TL-SG108-M2 | Switch | 8x RJ45 2.5Gb/s, Desktop, Unmanaged



link to the product:

<https://www.batna24.com/gb/p/switches/tp-link-tl-sg108-m2-switch-8x-rj45-25gb-s-desktop-unmanaged>

Price: **866.47 zł** gross / 704.45 zł net



Manufacturer: TP-LINK

Referention number: DNXGGIMJERMLMQ

Product features

Storage relative humidity (H-H)	5 - 90%
Power source	mains electricity
Height	35 mm
Input voltage	12 V
LED indicators	Yes
Wall mountable	Yes
Width	226 mm
Depth	131 mm
Auto-negotiation	Yes
Packet buffer memory	1.5 MB
Input current	1.5 A
Storage temperature (T-T)	-40 to 70 °C
Cables included	AC
Rack mounting	No
Fanless	Yes
Package weight	1350 g
Humidity measurement range	10 - 90%
Harmonized System (HS) code	85176990
Switching capacity	40 Gb/s
Networking standards	IEEE 802.3
Switch type	Unmanaged
10G support	No

Auto MDI/MDI-X	Yes
Operating temperature (T-T)	0 – 40 °C
Package depth	315 mm
Package height	70 mm
Heat dissipation	53.4 British thermal unit per hour
Package width	240 mm
Quality of Service (QoS) support	Yes
Flow control support	Yes
Jumbo frames	10000
Jumbo frames support	Yes
MAC address table	16000 entries
Power supply included	Yes
Power over Ethernet (PoE)	No
Store-and-forward	Yes
2.5G Ethernet (copper) ports quantity	8
Product colour	Black
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Basic switching RJ-45 Ethernet ports quantity	8

Full product description

Switch TP-Link TL-SG108-M2

TP-Link introduces the **TL-SG108-M2** desktop multi-gigabit switch, part of its Omada series of network devices. It features **8 2.5Gbps ports** that provide high performance for connected devices such as access points, servers, NAS devices and workstations.



Auto-negotiation speed and incredible throughput

Speed auto-negotiation technology is supported when connecting ports. It automatically selects the appropriate connection type by choosing from the following options: 100 Mbit/s; 1 Gbit/s; 2.5 Gbit/s. The total switching capacity of the device is **40 Gbit/s**, which is suitable for SMB network deployment as well as home use.



Category 6 cable support

Connections are made with minimal latency and avoid the use of expensive, standardized **Category 6 cabling for Gigabit Ethernet** and other physical-layer networking equipment, where there are more stringent technical requirements to avoid crosstalk and system noise than with Cat 5/5e and Cat 3 standards.



Wide range of switching scenarios

The **TL-SG108-M2 switch** enables ultra-fast data transfer between workstations. The multi-gigabit ports provide an efficient way to fully connect **network** access points to **WiFi 6**. The high-speed wired connection provides users with the ability to quickly back up workstations and quickly save files to a server or NAS. The **TL-SG108-M2 switch** is ergonomically designed. The fanless design ensures quiet operation. The rugged metal chassis distributes heat evenly and allows it to be placed anywhere - on a desk or on a wall. With auto-MDI/MDIX technology, users can eliminate the need for a crossover cable.



Main features

- Eight 2.5 Gbps ports
- Ultra fast connections
- The ideal equipment for many applications
- Trouble-free cabling
- Quiet operation
- Plug and Play
- Metal casing