



TP-Link TL-SG1210MP | Switch | 9x RJ45 1000Mb/s, 8x PoE+, 1x RJ45/SFP Combo



link to the product:

<https://www.batna24.com/gb/p/switches/tp-link-tl-sg1210mp-switch-9x-rj45-1000mb-s-8x-poe-1x-rj45-sfp-combo>

Price: **652.77 zł** gross / 530.71 zł net



Manufacturer: TP-LINK

Referention number: DNXGGIMJFRMLNP

Product features

Regulatory Approvals	CE, FCC
Storage relative humidity (H-H)	5 - 90%
Power source	mains electricity
Height	26 mm
LED indicators	Yes
Width	209 mm
Depth	126 mm
Auto-negotiation	Yes
Packet buffer memory	14.88 MB
Input current	2.43 A
Storage temperature (T-T)	-40 to 70 °C
Rack mounting	No
Fanless	Yes
Power consumption (max)	141.4 W
Package weight	1410 g
Humidity measurement range	10 - 90%
Harmonized System (HS) code	85176990
Switching capacity	20 Gb/s
Quick start guide	Yes
Networking standards	IEEE 802.3af
Switch type	Unmanaged
10G support	No

MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Auto MDI/MDI-X	Yes
Operating temperature (T-T)	0 – 40 °C
Package depth	315 mm
Package height	70 mm
Heat dissipation	482.17 British thermal unit per hour
Package width	240 mm
Total Power over Ethernet (PoE) budget	123 W
Flow control support	Yes
MAC address table	4000 entries
Power over Ethernet (PoE)	Yes
Combo SFP ports quantity	1
Power over Ethernet (PoE) power per port	30 W
Power over Ethernet plus (PoE+) ports quantity	8
Cable types supported	Cat3
Store-and-forward	Yes
Copper ethernet cabling technology	100BASE-TX
Product colour	Black
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	9

Full product description

TP-LINK TL-SG1210MP 10-port SWITCH

Dedicated 8 PoE ports (123W) for multiple applications. 802.3af/at PoE compliance allows **up to 30 watts** per PoE port. **The total power budget of 123W* for 8 PoE ports** opens up a wide range of applications such as surveillance in offices, dormitories and small businesses.

The device is fully compatible with IP cameras, access points, IP phones, computers, printers and other devices.



- 9 RJ45 gigabit ports and 1 SFP/RJ45 gigabit combo port
- 8 PoE ports transmit data and power over a single cable for a total power consumption of 123W*
- IEEE 802.3af/at PoE compliant, the switch supports up to 30W PoE power for each PoE port
- Data and power transmission range of up to 250 m in Extend Mode**
- Priority Mode provides high priority on ports 1-2 to ensure quality of sensitive applications
- Isolation Mode isolates client traffic with a single click to enhance security and performance
- Automatically restart failed or non-functioning PoE-powered devices with PoE Auto Recovery
- Plug and play with no configuration required
- Fanless design reduces power consumption and operates quietly in the field



System self-healing with PoE Auto Recovery

The switch **automatically** detects and reboots devices such as cameras and access points when they stop working or become unresponsive, ensuring stable operation of PoE-connected devices **without manual monitoring and rebooting**.

Durable metal housing

The internal components of the TL-SG1210MP are protected by a high-quality metal chassis that ensures a long product life. The TL-SG1210MP switch has passed a series of rigorous reliability tests, ensuring switching performance you can rely on.

