



**TP-Link TL-SG3428X | Switch |
JetStream, 24x RJ45
1000Mb/s, 4x SFP+, L2+**



link to the product:

<https://www.batna24.com/gb/p/switches/tp-link-tl-sg3428x-switch-jetstream-24x-rj45-1000mb-s-4x-sfp-l2>

Price: **1,291.71 zł** gross / 1,050.17 zł net



Manufacturer: TP-LINK

Referention number: DNXGGJJMGRMLPN

Product features

Storage relative humidity (H-H)	5 - 90%
Power source	mains electricity
Height	44 mm
LED indicators	Yes
Width	440 mm
Depth	180 mm
Virtual LAN features	Private VLAN
Packet buffer memory	12 MB
Storage temperature (T-T)	-40 to 70 °C
Cables included	LAN (RJ-45)
Rack mounting	Yes
Fanless	Yes
Power consumption (max)	23.6 W
GARP VLAN Registration Protocol (GVRP)	Yes
IPv4 & IPv6 features	IPv4/IPv6 access-control list (ACL)
Rate limiting	Yes
Authentication type	AAA
MIB support	Y
Console port	RJ-45/Micro-USB
Humidity measurement range	10 - 90%
Configuring Location Settings (CLI)	Yes
Switching capacity	128 Gb/s

Quick start guide	Yes
Networking standards	IEEE 802.3ab
Switch type	Managed
10G support	Yes
Loop protection	Yes
BPDU filtering/protection	Yes
Authentication	Guest VLAN
ARP inspection	Yes
Active link detection	Yes
SSH/SSL support	Yes
Number of VLANs	4000
Spanning tree protocol	Yes
Head-of-line (HOL) blocking	Yes
Broadcast storm control	Yes
Operating temperature (T-T)	0 - 45 °C
Heat dissipation	80.52 British thermal unit per hour
Quality of Service (QoS) support	Yes
VLAN support	Yes
Link aggregation	Yes
Management protocols	SNMPv1/v2c/v3, SNMP
Cloud-managed	Yes
IGMP snooping	Yes
SFP+ module slots quantity	4
Web-based management	Yes
Flow control support	Yes
Port mirroring	Yes
Jumbo frames	9000
Jumbo frames support	Yes
MAC address table	16000 entries
IPv4 routes	48
IPv6 routes	48
Power supply included	Yes
Power over Ethernet (PoE)	No
Number of static routes	48
AC input frequency	50 Hz
AC input voltage	100 V
Gigabit Ethernet (copper) ports quantity	24
System event log	Yes
DHCP features	DHCP client
Multicast Listener Discovery (MLD) snooping	Y
Store-and-forward	Yes
Product colour	Black
Power connector	AC-in jack
Switch layer	L2+/L3
IP-MAC-Port binding	Yes
Access Control List (ACL)	Yes
Policy-based routing	Yes
Multicast support	Yes

Static route	Yes
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	24