



**TP-Link TL-SG3452 | Switch |
JetStream, 48x RJ45
1000Mb/s, 4x SFP, L2,
Managed**



link to the product:

<https://www.batna24.com/gb/p/switches/tp-link-tl-sg3452-switch-jetstream-48x-rj45-1000mb-s-4x-sfp-l2-managed>

Price: **1,617.56 zł** gross / 1,315.09 zł net



Manufacturer: TP-LINK

Referention number: DNXGGHKNERMLOI

Product features

Regulatory Approvals	CE, FCC, RoHS
Storage relative humidity (H-H)	5 – 90%
Power source	mains electricity
Height	44 mm
Width	440 mm
Depth	220 mm
Virtual LAN features	Port-based VLAN
Storage temperature (T-T)	-40 to 70 °C
Cables included	AC
Rack mounting	Yes
Fanless	Yes
Power consumption (max)	34.86 W
GARP VLAN Registration Protocol (GVRP)	Yes
IPv4 & IPv6 features	IPv4/IPv6 access-control list (ACL)
Authentication type	AAA
MIB support	Y
Console port	RJ-45/Micro-USB
Humidity measurement range	10 – 90%
Configuring Location Settings (CLI)	Yes
Switching capacity	104 Gb/s
Quick start guide	Yes
Networking standards	IEEE 802.1D

Switch type	Managed
10G support	No
Loop protection	Yes
BPDU filtering/protection	Yes
Authentication	MAC-based authentication
ARP inspection	Yes
SSH/SSL support	Yes
Flash memory	32 MB
Number of VLANs	4000
Spanning tree protocol	Yes
Head-of-line (HOL) blocking	Yes
Broadcast storm control	Yes
Operating temperature (T-T)	0 - 40 °C
Heat dissipation	118.94 British thermal unit per hour
Quality of Service (QoS) support	Yes
Rack mount kit	Yes
VLAN support	Yes
Link aggregation	Yes
Management protocols	SNMPv1/v2c/v3, SNTp
Cloud-managed	Yes
IGMP snooping	Yes
IP routing	Yes
Web-based management	Yes
Flow control support	Yes
Port mirroring	Yes
Jumbo frames	9000
Jumbo frames support	Yes
MAC address table	16000 entries
IPv4 routes	48
IPv6 routes	48
Power supply included	Yes
Power over Ethernet (PoE)	No
Internal memory	256 MB
SFP module slots quantity	4
AC input frequency	50 Hz
AC input voltage	100 V
Gigabit Ethernet (copper) ports quantity	48
System event log	Yes
DHCP features	DHCP client
Multicast Listener Discovery (MLD) snooping	Y
Store-and-forward	Yes
Product colour	Black
Switch layer	L2+
IP-MAC-Port binding	Yes
Access Control List (ACL)	Yes
MAC address filtering	Yes
Policy-based routing	Yes
Multicast support	Yes

Static route	Yes
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Basic switching RJ-45 Ethernet ports quantity	48