



TP-Link TL-SM311LM | SFP Module | 1,25Gb/s, LC/UPC, 850nm, Multimode



link to the product:

<https://www.batna24.com/gb/p/sfp-modules/tp-link-tl-sm311lm-sfp-module-125gb-s-lc-upc-850nm-multimode>

Price: **69.40 zł** gross / 56.42 zł net



Manufacturer: TP-LINK

Referention number: DNXEDLHRIRMMIQ

Product features

Regulatory Approvals	FCC, CE
SFP transceiver type	Fiber optic
Storage relative humidity (H-H)	5 - 90%
CD-ROM interface type	mini-GBIC/SFP
Height	12.9 mm
Width	55.4 mm
Depth	13.7 mm
Storage temperature (T-T)	-40 - 80 °C
Compliance certificates	RoHS
Maximum data transfer rate	1250 Mb/s
Package weight	110 g
Humidity measurement range	10 - 90%
Fiber cable diameters supported (core/cladding)	50/125
Maximum operating temperature	70 °C
Harmonized System (HS) code	85369010
Networking standards	IEEE 802.3z
Operating temperature (T-T)	0 - 70 °C
Package depth	207 mm
Package height	38 mm
Minimum operating temperature	0 °C
Package width	38 mm
User guide	Yes

Fiber optic connector	LC (UPC)
Multi-mode fiber (MMF) supported	Yes
Single-mode fiber (SMF) supported	No
Wavelength	850 nm
Product colour	Metallic
Maximum transfer distance	550 m

Full product description

Multi-mode optical fibre module MiniGBIC TL-SM311LM

The **TL-SM311LM fiber optic module** meets the requirements of LAN, is designed to **enlarge the transfer range of intelligent and manageable switches** to several or even several dozen kilometers. Depending on the demand and in order to reduce costs, users may resign or choose elements to be used in fiber optic modules. The device uses the **IEEE 802.3z** standard and its transmission speed can be **1.25 Gb/s**. The module cooperates with TP-Link switches having gigabit **SFP** slots.

