



TP-Link TL-SM311LS | SFP Module | 1,25Gb/s, LC/UPC, 10km, 1310nm, Single mode



link to the product:

<https://www.batna24.com/gb/p/sfp-modules/tp-link-tl-sm311ls-sfp-module-125gb-s-lc-upc-10km-1310nm-single-mode>

Price: **60.87 zł** gross / 49.49 zł net



Manufacturer: TP-LINK

Referention number: DNXEDLHRJRMMP

Product features

SFP transceiver type	Fiber optic
Storage relative humidity (H-H)	5 - 90%
CD-ROM interface type	mini-GBIC
Height	12.9 mm
Width	55.4 mm
Depth	14.6 mm
Storage temperature (T-T)	-40 - 85 °C
Compliance certificates	CE
Maximum data transfer rate	1250 Mb/s
Package weight	110 g
Humidity measurement range	10 - 90%
Fiber cable diameters supported (core/cladding)	9/125 μm
Networking standards	IEEE 802.3z
IFU / User manual	Yes
Operating temperature (T-T)	0 - 70 °C
Package depth	207 mm
Package height	38 mm
Package width	38 mm
Hot-swap	Yes
Brand compatibility	MSA Compliant
Fiber optic connector	LC
Duplex system	Full

Single-mode fiber (SMF) supported	Yes
Wavelength	1310 nm
Digital Diagnostics Monitoring (DDM)	Yes
Product colour	Silver
Maximum transfer distance	20000 m
Hot-Plug support	Yes
SFP transceiver standard	LX
Fiber ethernet cabling technology	1000BASE

Full product description

MiniGBIC TL-SM311LS single-mode optical fibre module

The **TL-SM311LS** fiber optic module meets LAN requirements and is designed to **extend the transfer range of intelligent and manageable switches** to several or even several dozen kilometers. Depending on the demand and in order to reduce operating costs, users may resign or choose the elements to be used in fiber optic modules. The device uses the **IEEE 802.3z** standard and its transmission speed is **1.25 Gb/s**. The module cooperates with TP-Link switches, which have gigabit **SFP** slots.

