



TP-Link TL-SM321A | SFP Module | 1,25Gb/s, LC/UPC, 10km, 1550/1310nm, Single mode

6 935364 030513 >

link to the product:

<https://www.batna24.com/gb/p/sfp-modules/tp-link-tl-sm321a-sfp-module-125gb-s-lc-upc-10km-1550-1310nm-single-mode>

Price: **82.59 zł** gross / 67.15 zł net



Manufacturer: TP-LINK

Referention number: DNXEDLHRKRMKO

Product features

Regulatory Approvals	FCC, CE
SFP transceiver type	Fiber optic
Storage relative humidity (H-H)	5 - 90%
CD-ROM interface type	SFP
Height	12.9 mm
Width	55.4 mm
Depth	12.9 mm
Storage temperature (T-T)	-40 - 80 °C
Maximum data transfer rate	1250 Mb/s
Package weight	60 g
Humidity measurement range	10 - 90%
Fiber cable diameters supported (core/cladding)	9/125 µm
Networking standards	IEEE 802.3z
Plug and Play	Yes
Operating temperature (T-T)	0 - 70 °C
Package depth	122.5 mm
Package height	38.5 mm
Package width	81.5 mm
Fiber optic connector	LC (UPC)
Single-mode fiber (SMF) supported	Yes
Product colour	Metallic
Maximum transfer distance	10000 m

Rx wavelength (max)	1310 nm
Tx wavelength (max)	1550 nm

Full product description

Two-way SFP module TL-SM321A 1000BASE-BX WDM

TP-LINK's TL-SM321A is a **single-mode SFP** module using the latest **1000 Base-BX** standard, which performs bidirectional transmission on a single fiber. The SFP optical insert operates at 1550 nm and 1310 nm wavelengths. Single-mode SFP module TL-SM321A enables transmission over a distance **up to 10 km** and the speed of this transmission reaches **up to 1.25 Gbps**. SFP TL-SM321A inserts are equipped with LC/UPC connectors and work with many TP-LINK devices such as routers, switches and media converters.



Special features

- Support for bidirectional WDM technology using a single fiber optic fibre
- TX: 1550 nm/RX: 1310 nm
- Internal power supply +3.3 V
- In pairs with TL-SM321B
- Plug-and-Play
- Compatible products: TL-SG5428, TL-SG3210/3216/3424/3424P, TL-SL3428/3452, TL-SG2216/2424, TL-SL2210WEB/2218WEB/2428WEB/2452WEB, TL-SL1351 and MC200L