



Ubiquiti NSM2 | CPE |
NanoStation, 2,4GHz, 2x RJ45
100Mb/s, 11dB



link to the product:
<https://www.batna24.com/gb/p/radio-lines/ubiquiti-nsm2-cpe-nanostation-24ghz-2x-rj45-100mb-s-11db>

Price: **380.56 zł** gross / 309.40 zł net



Manufacturer: UBIQUITI
Referention number: DNXIHMSKEHK

Product features

Regulatory Approvals	FCC 15.247, IC RS210, CE, RoHS
Product type	Network bridge
Height	294 mm
Width	80 mm
Depth	31 mm
Connectivity technology	Wired & Wireless
RAM type	SDRAM
Power consumption (max)	8 W
Humidity measurement range	5 – 95%
Harmonized System (HS) code	85176990
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN (RJ-45) ports	2
Antenna gain level (max)	11.2 gain
Flash memory	8 MB
Processor family	Atheros
Material	Plastic
Operating temperature (T-T)	-30 to 75 °C
Cabling technology	10/100Base-T(X)
Processor frequency	400 MHz
Power over Ethernet (PoE)	Yes
Internal memory	32 MB
Wi-Fi band	Single-band (2.4 GHz)
Wi-Fi	Yes

Ethernet LAN	Yes
Power over Ethernet (PoE) voltage	24 V
Processor model	MIPS 24Kc
Product colour	White
Mounting hardware type	Pole
Product weight	400 g

Full product description

Compact CPE design

The **NanoStation M** has a **CPE** design that has expanded the global wireless internet industry.

Plug and Play installation

NanoStation M requires no special tools, just one screw on the pole.

Universal application

NanoStation M can be used for point-to-point (PtP) connection or as airMAX **CPE**.

Dual Ethernet connection

With the software-supported PoE output, a second Ethernet port can **power an external device**, such as a PoE external camera, for trouble-free video recording.

Efficient airOS functions

Ubiquiti's comprehensive **airOS** software technology enables a powerful **multi-point external network**. airOS provides features such as wireless network settings, bridge or routing configuration and system management services.



Advanced software

Ubiquiti's **airMAX** technology has been proven in millions of products worldwide, demonstrating exceptional performance in outdoor conditions. **The TDMA** airMAX protocol enables unprecedented scalability, **high speed and low latency** in unlicensed, multipoint networks.



Window or wall mounting kit

Use the NanoStation Mount to quickly mount NanoStationM on a window or wall. The 180° vertical or horizontal adjustment allows **any positioning**.

