



Ubiquiti UP-SuperLink | Gateway for UniFi Protect sensors | Bluetooth 5.2, SuperLink



link to the product:

<https://www.batna24.com/gb/p/routers/ubiquiti-up-superlink-gateway-for-unifi-protect-sensors-bluetooth-52-superlink>

Price: **533.51 zł** gross / 433.75 zł net



Manufacturer: UBIQUITI

Referention number: DNXXGILPFRMMIL

Product features

Height	159.3 mm
Antenna type	External
LED indicators	Status
Width	81.9 mm
Depth	26 mm
Compliance certificates	CE
Power consumption (max)	3.4 W
Humidity measurement range	10 - 90%
Ethernet LAN (RJ-45) ports	1
Antenna gain level (max)	3 gain
Operating temperature (T-T)	0 - 40 °C
Reset button	Yes
Power over Ethernet (PoE)	Yes
Bluetooth version	5.2
Bluetooth	Yes
Antennas quantity	1
Bluetooth Low Energy (BLE)	Yes
Product colour	White
Mounting hardware type	DIN-rail/Wall mounting
Control panel	No
Product weight	179 g

Full product description

Ubiquiti UP-SuperLink - Gateway for UniFi Protect Sensors

Ubiquiti UP-SuperLink is an advanced gateway designed to integrate with UniFi Protect sensors, offering Bluetooth 5.2 and SuperLink communication. With support for 96 SuperLink sensors and 7 Bluetooth devices, it provides efficient and stable data transmission for more effective site monitoring.



Efficient communication and support for multiple devices

The **Ubiquiti UP-SuperLink** allows simultaneous support of up to 96 SuperLink sensors and 7 **Bluetooth 5.2** devices, significantly increasing monitoring coverage. **SuperLink technology** provides greater range and higher transmission power, making it possible for the gateway to communicate with sensors even in hard-to-reach areas. **Support for the Bluetooth 5.2 protocol** further improves the stability of connections and enables fast detection and pairing of devices.



PoE power supply and additional connection options

The **UP-SuperLink** offers power over **PoE**, which eliminates the need for additional cables and makes the device easy to integrate into existing network infrastructure. Alternatively, it can be powered via a **USB-C port** (5V, 1A) for greater installation flexibility. With a low power consumption of **3.4W**, the device works efficiently without overloading the power grid.



SuperLink - The new generation of connectivity for sensors

SuperLink technology is a proprietary Ubiquiti standard that offers longer range and better transmission stability compared to classic Bluetooth. With a **maximum transmit power of 27 dBm**, the signal can penetrate walls and obstacles, allowing sensors to be placed in different parts of a facility without losing connectivity. **Support for up to 96 sensors** makes it ideal for monitoring large spaces.



Easy installation and integration with UniFi Protect

The **UP-SuperLink** works with the **UniFi Protect** system, allowing you to manage your sensors from a mobile app or web browser. With **wall or DIN-rail** mounting , the unit can be easily adapted to any installation configuration. **A single blue and white LED backlight** indicates the device's status, and a reset button allows for a quick reset to factory settings.

