



Cisco CBS350-16XTS | Switch | 8x 10G RJ45, 8x SFP+



link to the product:

<https://www.batna24.com/gb/p/switches/cisco-cbs350-16xts-switch-8x-10g-rj45-8x-sfp>

Price: **10,195.49 zł** gross / 8,289.02 zł net



Manufacturer: CISCO

Referention number: DNXXGIIIPFRMLPP

Product features

Regulatory Approvals	UL (UL 60950), CSA (CSA 22.2), FCC 15 (CFR 47) A
Storage relative humidity (H-H)	10 - 90%
Height	44 mm
LED indicators	Yes
Routing protocols	RIP-2
Width	440 mm
Depth	257 mm
Security algorithms	802.1x RADIUS
Mean time between failures (MTBF)	798504 h
VLAN mapping type	1:1 VLAN mapping
Virtual LAN features	IP subnet-based VLAN
Packet buffer memory	3 MB
Storage temperature (T-T)	-25 to 70 °C
Cables included	AC
Rack mounting	Yes
Compliance certificates	CE
GARP VLAN Registration Protocol (GVRP)	Yes
Rate limiting	Yes
Authentication type	IEEE 802.1x
Console port	RJ-45
Humidity measurement range	10 - 90%
USB 2.0 ports quantity	1

Redundant fans support	Yes
Configuring Location Settings (CLI)	Yes
Harmonized System (HS) code	85176990
Switching capacity	320 Gb/s
Quick start guide	Yes
Networking standards	IEEE 802.1ab
Switch type	Managed
10G support	Yes
Loop protection	Yes
BPDU filtering/protection	Yes
Authentication	Guest VLAN
Access Control List (ACL) rules	1024
ARP inspection	Yes
Active link detection	Yes
Cable length detection	Yes
Flash memory	256 MB
Number of VLANs	4094
Spanning tree protocol	Yes
Head-of-line (HOL) blocking	Yes
Broadcast storm control	Yes
Operating temperature (T-T)	0 - 50 °C
Heat dissipation	196.88 British thermal unit per hour
Quality of Service (QoS) support	Yes
Rack mount kit	Yes
VLAN support	Yes
Link aggregation	Yes
Reset button	Yes
Management protocols	SNMP v1/2c/3, Telnet, HTTP/HTTPS, SSH, RADIUS, BOOTP, SNTP
Firmware upgradeable	Yes
IGMP snooping	Yes
SFP+ module slots quantity	8
IP routing	Yes
Processor frequency	800 MHz
Web-based management	Yes
Flow control support	Yes
Port mirroring	Yes
Noise level	39.1 decibel
Jumbo frames	9000
Jumbo frames support	Yes
MAC address table	16000 entries
Power supply included	Yes
Power over Ethernet (PoE)	No
Internal memory	512 MB
Number of IP interfaces	128
Number of static routes	990
AC input frequency	50 Hz
Number of queues	8

AC input voltage	100 V
System event log	Yes
Cable types supported	Cat5e
DHCP features	DHCP relay
Built-in processor	Yes
Multicast Listener Discovery (MLD) snooping	MLD v1/2
Copper ethernet cabling technology	1000BASE-T
10G Ethernet (copper) ports quantity	8
Product colour	Black
Physical stacking (units)	4
Switch layer	L3+
IP-MAC-Port binding	Yes
Access Control List (ACL)	Yes
Policy-based routing	Yes
Multicast support	Yes
Static route	Yes
Number of power supply units	1
Basic switching RJ-45 Ethernet ports type	10G Ethernet (100/1000/10000)
Basic switching RJ-45 Ethernet ports quantity	8
Stackable	Yes
Redundant power supply (RPS) support	No
Sustainability compliance	Yes
Product weight	3790 g