



Cisco RV130 | Router | 4x RJ45 1000Mb/s, 1x WAN, 1x USB



link to the product:

<https://www.batna24.com/gb/p/routers/cisco-rv130-router-4x-rj45-1000mb-s-1x-wan-1x-usb>

Price: **250.24 zł** gross / 203.45 zł net



Manufacturer: CISCO

Referention number: DNXGFOQMCRMNGN

Product features

Regulatory Approvals	FCC, CE, IC
Storage relative humidity (H-H)	5 – 90%
Output voltage	12 V
LED indicators	Yes
Firewall	Yes
Security algorithms	AES
Input current	2 A
Storage temperature (T-T)	-20 to 70 °C
Rack mounting	No
Humidity measurement range	10 – 85%
Networking standards	IEEE 802.1D
Ethernet LAN (RJ-45) ports	4
DC-in jack	Yes
Operating temperature (T-T)	0 – 40 °C
Cabling technology	10/100/1000Base-T(X)
Supported network protocols	PPPoE, PPTP, L2TP, DNS, IGMP, RSTP, NAT, PAT, SIP, ALG
Ethernet interface type	Gigabit Ethernet
On/off switch	Yes
Ethernet LAN	Yes
Gigabit Ethernet (copper) ports quantity	4
Product colour	Black
Network address translation (NAT)	Yes

Ethernet WAN	Yes
DHCP client	Yes
DHCP server	Yes

Full product description

Cisco RV130 VPN router

The **Cisco RV130** router provides reliable and **efficient network communication**, both in and out of the office. It is a reliable firewall and VPN for **secure communication**.

Featuring a built-in **4-port** Managed **Gigabit Ethernet** switch that allows you to connect network devices and transfer files and data at high speeds. Setup doesn't take long, Configuring the router will get you up and running in **minutes**.



Main features

1. Interfaces: 4 x RJ-45 10/100/1000 Mbps LAN; 1 x RJ45 10/100/1000 Mbps GE WAN; 1 x USB;
2. LAN and WAN ports: Gigabit Ethernet;
3. 3G/4G/LTE USB;
4. Operating System: Linux;
5. Support for PPTP, L2TP, ICMP/IP IPsec, PPPoE, DHCP, DDNS, Bonjour;
6. IPsec VPN throughput (3DES, AES): 50 MB/s;
7. IPsec VPN security;
8. Control: Web browser, Bonjour, Universal Plug and Play (UPnP);
9. NAT throughput: 800 MB/s;
10. IPsec VPN Firewall: 10 IPsec Firewall tunnels;
11. Encryption standard: 3DES triple encryption, AES advanced encryption standard.

