



Extralink 37U 600x1000 Black | Rackmount cabinet | standing



link to the product:

<https://www.batna24.com/gb/p/rack-cabinets/extralink-37u-600x1000-black-rackmount-cabinet-standing>

Price: **2,148.99 zł** gross / 1,747.15 zł net

Manufacturer: EXTRALINK



Referention number: DNXGFMKMMRMNH

Information:

The standing EXTRALINK 37U rack cabinet with dimensions of 600 × 1000 mm is a robust solution for offices, server rooms and CCTV installations. Made of cold-rolled steel, it ensures durability and stability, while the front doors made of tempered glass can open to the left or right. Clear height markings make equipment installation easier, and 37U of space provides plenty of room for infrastructure expansion. Removable side panels with locks and keys make servicing easier, 4 cable entry points in the lower panel help with neat cable routing, and 4 fan mounting positions in the upper section support effective cooling. Adjustable feet and castors increase ease of use.

Product features

Height	1765 mm
Width	600 mm
Depth	1000 mm
Built-in UPS	No
Temperature sensor	No
Cooling type	Passive
Key lock	Yes
Rack rails	Yes
Material	Glass
Colour	Black
Rack capacity	37U
Maximum weight	1200 kg

Size (imperial)	19 "
Screws included	Yes
Nuts included	Yes
Soundproof	No
Side panel key lock	Yes
Front door key lock	Yes
Back door key lock	Yes
Side panels included	Yes
Removable side panels	Yes
Removable front door	Yes
Removable back door	Yes
Side panel construction	Metal
Front door construction	Glass
Back door construction	Metal
Product colour	Black
Frame type	Closed
Type	Wall mounted rack
Baby unit batteries included	No

Full product description

EXTRALINK rack, 37U, 600x1000, standing

The **Extralink** rack cabinet is designed for offices, network server rooms and CCTV control rooms. The external walls are made of cold rolled steel sheet, while the front door has a tempered glass pane with the possibility of opening to the left or right side.

Extralink network cabinet 37HE

upright installation



The network cupboard is designed in offices, network servers and CCTV control rooms.



The outer walls are made of cold-rolled sheet steel.



Fitted with tempered glass, the front door may be opened to the left or right.



Clearly marked cabinet height

Vertical rails have the appropriate height marking, which is as high as **37U (unit)**, which provides sufficient space for the installation of many devices for our infrastructure. The total height of the cabinet is **176.5 cm**.

NETWORK CUPBOARD

floor standing

37U 19"

Maximum
weight



1765mm

1000mm

600mm

Easy removal of side walls

Snap fasteners on the side walls allow for their disassembly. **Locks and keys are included.**

NETWORK CABINET 37HE

Removable side panels for easy maintenance



Front and rear doors



Adjustable cable entry dimensions for top cover and base plate



Front door key lock



Front door with small tempered glass lock



Adjustable feet, durable castors



Door can be opened to the left and right

Easy cable routing

The lower panel has as many as **4 culverts** to pull out the cables, thus reducing the risk of squeezing or tangling them.

The task of network enclosures is to protect equipment and guarantee stable functioning and maintain order in every sphere.



Fan-installed ceiling

On the ceiling of the cabinet there are **4 spaces for installing fans** for better cooling of the devices, as well as **additional conduit** for pulling out cables.

Extralink has accessories for its cabinet series, you can find in our range:

- shelves, enclosures, cable organisers
- cooling accessories, ventilation panels, thermostats
- assembly aids



Features

- Front and rear doors
- Tempered glass front door with small lock
- Reversible right or left hand door
- Excellent design, precise dimensions, careful workmanship
- Adjustable feet and heavy duty casters are available simultaneously
- Cable entry for top cover and bottom plate with adjustable dimensions
- Reliable body connection with the baying kit
- Removable side panels for easy maintenance