



Extralink Chiron Pro | PoE Switch | 24x RJ45 1000Mb/s PoE, 4x SFP+, L3, managed, 370W



link to the product:

<https://www.batna24.com/gb/p/switches/extralink-chiron-pro-poe-switch-24x-rj45-1000mb-s-poe-4x-sfp-l3-managed-370w>

Price: **1,660.50 zł** gross / 1,350.00 zł net

Manufacturer: EXTRALINK



Referention number: DNXGGJJQMRMMOJ

Product features

Power source	mains electricity
Height	44 mm
Width	440 mm
Depth	210 mm
Virtual LAN features	Voice VLAN
Packet buffer memory	1.5 MB
Rack mounting	Yes
Switching capacity	128 Gb/s
Networking standards	IEEE 802.3af
Switch type	Managed
10G support	Yes
Rack rails	Yes
Flash memory	16 MB
Quality of Service (QoS) support	Yes
Rack mount kit	Yes
VLAN support	Yes
Total Power over Ethernet (PoE) budget	370 W
IP routing	Yes
Web-based management	Yes
Noise level	37.5 decibel

Jumbo frames	9000
MAC address table	16000 entries
Power supply included	Yes
Power over Ethernet (PoE)	Yes
Installed SFP+ modules quantity	4
DHCP features	DHCP client
Product colour	White
Power connector	AC-in jack
Switch layer	L3+
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Watch case material	Metal
Basic switching RJ-45 Ethernet ports quantity	24
Stackable	No
Product weight	3000 g

Full product description

Extralink Chiron - gigabit PoE switch with SFP ports

Extralink Chiron Pro is a 24-port **Layer 3** switch with next-generation PoE power. It is targeted at IP MAN (metropolitan area network), government and corporate networks, Internet cafes. It is developed based on high-performance hardware and supports features such as efficient ACLs, flexible QinQ, 1:1 or N:1 VLAN switching, Ethernet OAM, carrier-level QoS and industry-level 10GE Ether-ring. It also supports Layer 3 routing protocol.

High reliability

Based on an advanced distribution mechanism and an efficient cross-physical link aggregation function, the logic control plane, service control plane and service data plane are separated. This allows **Extralink Chiron Pro** to support continuous routing redirection at Layer 3, avoiding service interruption due to a single failure.

Telecommunications level Ethernet switch

Chiron Pro supports telecom-level Ethernet protection protocol with less than 50 ms protection offset time, STP/RSTP/MSTP, active and backup uplinks, and LACP link aggregation to ensure high service reliability. Provides an excellent Ethernet OAM mechanism for real-time network health monitoring for rapid problem localization and detection. Supports **In-Service Software Upgrade (ISSU)** to ensure uninterrupted data transfer during system upgrades. Supports various **L2 multicast** functions, including **IGMP-Snooping**, fast-leave and trans-vlan.

Flexible and convenient management and maintenance

- It supports management modes such as console port, Telnet, SSH, etc.
- Supports WEB management mode, which is easy and efficient, making installation and debugging convenient
- Support for file upload/download management via TFTP protocol
- Supports ISSU (In-Service Software Upgrade).

QoS rules at the operator level

- Supports priority retagging and complex flow classification based on VLAN, MAC, source address, destination address, IP or priority to enhance service levels
- Provides flexible bandwidth control policies and supports port/flow-based flow limit, and provides line speed redirection of each port to ensure high-quality video, audio and data services
- Supports 8 priority queues per port
- Supports multiple queue scheduling algorithms, e.g. SP, WRR and SP WRR

Comprehensive IPv6 solutions

- Supports IPv6 protocol suite, IPv6 neighbor detection, ICMPv6, path MTU detection, etc.
- Supports Ping, Traceroute, Telnet, SSH, ACL based on IPv6, meeting IPv6 network requirements for hardware management and service control

Excellent security mechanisms

The advanced hardware infrastructure design implements tier-based packet scheduling and packet protection, prevents DoS-/TCP attacks related to SYN flood, UDP flood, broadcast storm or heavy traffic, and supports tier-based command-line protection, giving different levels of users different management privileges.

Intelligent PoE

The **Extralink Chiron Pro** supports the **IEEE 802.3af/at PoE** standard with a total maximum power of **370W**.