



8F EXTRALINK AERIAL FIBER OPTIC CABLE 8J SM G652 D DIAMETER 6,3MM 1,0KN WITH FRP FUJIKURA FIBERS INSIDE

2,00 PLN brutto
1,63 PLN netto

Producent: EXTRALINK

Price for 1m **Cable packed on spool 2000m Fujikura fibers inside** Overview: 8F EXTRALINK cable for suspension and operation on the supports of overhead communication lines, urban electric transport and overhead transmission lines under conditions of loads from wind, ice, temperature and their combinations. Cable structure: 1 Optical fibers

2 Thixotropic hydrophobic aggregate

3 Longitudinally located glass ropes

4 Polymer tube

5 High density polyethylene sheath Specifications:

| | |
|---|-----------------------|
| Transfer | |
| Coefficient of attenuation at reference wavelengths, dB / km: - 1310 nm -1550 nm | 0,36 0,22 |
| | |
| Coefficient of chromatic dispersion at reference wavelengths, ps / (nm km): - 1310 nm -1550 nm | 3,5 18 |
| | |
| Oversized | |
| Number of OF in cable | 8 |
| Weight of cable, kg / km | 20 |
| Diameter of cable, mm | 6,3 |
| Mechanical and climatic | |
| Minimum bending radius, mm | 20 diameters of cable |
| Allowable tensile force, kN | 1,0 |
| Allowable crushing force, not more, N / 100 mm | 1000 |
| Resistance to impacts with initial energy, J | 10 (25 strikes) |
| Operating temperature range, °C | -40°C - +60°C |
| Storage temperature, °C | -50°C - +60°C |
| Mounting temperature, °C | -10°C - +60°C |
| Application | |
| Cable length, km | 2 |

| | |
|----------------|----------------|
| Do montażu | Napowietrznego |
| Liczba włókien | 8F |
| Rodzaj włókna | G.652.D |
| Średnica kabla | 5.1 - 7.0mm |



