

# Cisco 350X Series Stackable Managed Switches

---

# Contents

Managed Switches That Provide the Ideal Combination of Features and Affordability	3
Cisco 350X Series Stackable Managed Switches	3
Features and Benefits	4
Ordering Information	25
Cisco Capital	27
For More Information	27

---

## Managed Switches That Provide the Ideal Combination of Features and Affordability

To stay ahead in a competitive marketplace, small businesses need to make every dollar count. That means getting the most value from your technology investments, but it also means making sure that employees have fast, reliable access to the business tools and information they need. Every minute an employee waits for an unresponsive application – and every minute your network is down – has an impact on your bottom line. The importance of maintaining a strong and dependable business network only grows as your business adds more employees, applications, and network complexity.

When your business needs advanced security and features but affordability and value is key, you're ready for the new generation of Cisco® Small Business managed switches: The Cisco 350X Series.

### Cisco 350X Series Stackable Managed Switches

The Cisco® 350X Series Stackable Managed Switches (Figure 1) are a new line of stackable managed Ethernet switches that provide the rich capabilities you need to support a more demanding network environment at a very affordable price. The 350X models provide 8 to 48 ports of Gigabit, Multigigabit Ethernet, or 10-Gigabit speed. The 10-Gigabit models provide 8, 12, 24, or 48 ports of all 10-Gigabit Ethernet, providing a solid foundation and more than enough bandwidth for your business applications today and in the future. These switches are easy to deploy and manage without a large IT staff.



**Figure 1.**  
Cisco 350X Series Stackable Managed Switches

Cisco 350X Series switches are designed to protect your technology investment as your business grows. Unlike switches that claim to be stackable but have elements that are administered and troubleshot separately, the Cisco 350X Series provides true stacking capability, allowing you to configure, manage, and troubleshot multiple physical switches as a single device and more easily expand your network.

---

A true stack delivers a unified data and control plane, in addition to management plane, providing flexibility, scalability, and ease of use because the stack of units operates as a single entity. The switches also protect your technology investment with an enhanced warranty, dedicated technical support, and the ability to upgrade equipment in the future. Overall, the Cisco 350X Series provides the ideal technology foundation for a growing business.

## Features and Benefits

Cisco 350X Series switches provide the advanced feature set that growing businesses and high-bandwidth applications and technologies require. These switches can improve the availability of your critical applications, protect your business information, and optimize your network bandwidth to more effectively deliver information and support applications.

### High-Performance 10 Gigabit Ethernet

Cisco 350X Series switches break the barrier of 10 Gigabit Ethernet adoption by providing affordable and powerful features for growing small and medium businesses networks. With the 10-Gigabit ports, in both copper and fiber, you can easily and cost-effectively enable 10G connections to servers and network storage devices with standard RJ45 Ethernet cable. You can also aggregate 10G SFP+ fiber connections to build a high-performance backbone to dramatically increase the overall speed of your network.

### Multigigabit Performance

Network needs are changing quickly. Thanks to evolving wireless standards and the rising number of wireless devices, keeping up with data rates and growing traffic can be a challenge. Your traditional Ethernet infrastructure can support speeds up to 1 Gigabit per second (Gbps), but competing today requires much more capacity. One option is completely replacing your older cabling infrastructure and upgrading your hardware. But wouldn't it be better to increase network speed and traffic capacity in a way that's quick, inexpensive, and efficient?

Cisco's Multigigabit Ethernet switches offer just that: an easy-to-deploy, budget-friendly solution that allows you to increase network speed and bandwidth using your existing cables. By partnering with other industry leaders to form the NBASE-T Alliance, Cisco uses NBASE-T technology to help you get more out of your existing infrastructure. Save time and money by avoiding upgrades and extending the life of your installed cable plants. And discover the benefits of meeting consumer demand for increased bandwidth and speeds without a large initial investment.

Multigigabit Ethernet technology uses capabilities in your existing cabling infrastructure to meet bandwidth requirements and provide up to five times the performance. The technology enables intermediate data rates of 2.5 and 5 Gbps to ease the jump between traditional rates of 1 Gbps and 10 Gbps. These intermediate rates run on most installed cables and preserve older UTP wiring, which is good for 802.11ac wireless LAN applications.

The technology also supports Power over Ethernet (PoE) forms, including PoE+ and 60W PoE. Cisco Multigigabit Ethernet switches help you avoid having to run multiple cables between switches and access points and let your networks welcome next-generation traffic speeds and data rates.

---

## Easy configuration and management

Cisco 350X Series switches are designed to be easy to use and manage by small business customers or the partners that serve them.

- Smart Network Application (SNA) is an innovative network-level monitoring and management tool embedded in the Cisco 100 to 500 Series switches. It can discover network topology, display link status, monitor events, apply configurations, and upgrade software images across multiple switches in the network.
- The FindIT Network Manager and Probe are designed to manage Cisco 100 to 500 Series switches, routers, and wireless access points. They let you proactively manage the network instead of just reacting to events. Cisco 250 Series switches support the embedded FindIT Network Probe, eliminating the need to set up a separate hardware or virtual machine on site. For more information, visit <https://www.cisco.com/c/en/us/products/cloud-systems-management/findit-network-management/index.html>.
- The FindIT Network Discovery Utility works through a simple toolbar on the user's web browser to discover Cisco devices on the network and display basic device information, inventory, and new firmware updates to aid in the configuration and speed the deployment of Cisco Small Business products. For more information, visit <https://www.cisco.com/c/en/us/products/cloud-systems-management/small-business-findit-network-discovery-utility/index.html>.
- Simple or advanced-mode graphic user interfaces reduce the time required to deploy, troubleshoot, and manage the network. Configuration wizards simplify the most common configuration tasks and provide the ultimate tool for anyone to set up and manage the network.
- Cisco Smartports technology provides more advanced capabilities and hands-on control by automatically configuring ports with specific levels of security, QoS, and availability according to the type of connected device, based on Cisco best practices and pretested configurations. The Auto Smartports feature automatically applies the intelligence delivered through the Smartports roles to the port based on the device types discovered over Cisco Discovery Protocol or LLDP-MED. This capability facilitates zero-touch deployments.
- The USB port on the front panel of the switch enables easy image and configuration transfer for faster deployment or upgrades.

## Power over Ethernet Plus (PoE+) and 60W PoE

PoE technology simplifies the deployment of IP phones and wireless access points by allowing you to connect and power network endpoints over a single Ethernet cable, without having to install separate power supplies. The 350X Series switches support 15W Power over Ethernet (PoE) and 30W Power over Ethernet Plus (PoE+). The switches also support 60W PoE on selected ports to power compact switches, high-power wireless access points, or connected lighting. The PoE power is intelligently managed in a way such that only the amount of power needed by endpoints is delivered to it and not wasted. As a result, the switches can support devices that require more power, such as 802.11ac wireless access points, video-based IP phones, surveillance cameras, and more. The PoE features in the 350X Series switches are also fully backward compatible with 802.3af PoE, 802.3at PoE+, and Cisco legacy PoE protocols.

---

## High Reliability and Resiliency

In a growing business where availability 24 hours a day, 7 days a week is critical, you need to assure that employees can always access the data and resources they need. In these environments, stackable switches can play an important role in eliminating downtime and improving network resiliency. For example, if a switch within a Cisco 350X Series stack fails, another switch immediately takes over, keeping your network up and running. You can also replace individual devices in the stack without taking your network offline or affecting employee productivity.

The Cisco 350X Series also supports dual images, allowing you to perform software upgrades without having to take the network offline or worry about the network going down during the upgrade.

## Simplified IT Operation

Cisco 350X Series switches help optimize your IT operations with built-in features that simplify and streamline day-to-day network operation:

- True stacking allows you to troubleshoot, configure, and manage multiple physical switches as a single entity.
- Cisco switches use common chipsets/software across all switching portfolios, so all Cisco switches within a category support the same feature set, making it easier to manage and support all switches across the network.

## True Stacking

Some switches claim to support stacking but they only support “clustering” or “virtual stacking,” which means each switch must still be managed and configured individually. They cannot be managed as a single entity or device. Cisco 350X Series switches provide true horizontal stacking, enabling you to configure, manage, and troubleshoot multiple physical switches as a single device, with a single IP address, for up to 4 units and up to 208 ports.

A true horizontal stack delivers a unified data and control plane, in addition to management plane, providing flexibility, scalability, and ease of use because the stack of units operate as a single entity constituting all the ports of the stack members. This capability can radically reduce complexity in a growing network environment while improving the resiliency and availability of network applications. True stacking also provides other cost savings and administrative benefits through features such as cross-stack QoS, VLANs, LAGs, and port mirroring, which clustered switches can't support.

## Strong Security

Cisco 350X Series switches provide the advanced security features you need to protect your business data and keep unauthorized users off the network:

- Embedded Secure Sockets Layer (SSL) encryption protects management data traveling to and from the switch.
- Extensive Access Control Lists (ACLs) restrict sensitive portions of the network to keep out unauthorized users and guard against network attacks.
- Guest VLANs let you provide Internet connectivity to nonemployee users while isolating critical business services from guest traffic.

- Support for advanced network security applications such as IEEE 802.1X port security tightly limits access to specific segments of your network. Web-based authentication provides a consistent interface to authenticate all types of host devices and operating systems, without the complexity of deploying IEEE 802.1X clients on each endpoint.
- Advanced defense mechanisms, including dynamic Address Resolution Protocol (ARP) inspection, IP Source Guard, and Dynamic Host Configuration Protocol (DHCP) snooping, detect and block deliberate network attacks. Combinations of these protocols are also referred to as IP-MAC port binding (IPMB).
- IPv6 First Hop Security extends the advanced threat protection to IPv6. This comprehensive security suite includes ND inspection, RA guard, DHCPv6 guard, and neighbor binding integrity check, providing unparalleled protection against a vast range of address spoofing and man-in-the-middle attacks on IPv6 networks.
- Time-based ACLs and port operation restrict access to the network during pre-designated times such as business hours.
- Uniform MAC address-based security can be applied automatically to mobile users as they roam between wireless access points.
- Secure Core Technology (SCT) helps ensure that the switch is able to process management traffic in the face of a Denial-of-Service (DoS) attack.
- Private VLAN Edge (PVE) provides Layer 2 isolation between devices on the same VLAN.
- Storm control can be applied to broadcast, multicast, and unknown unicast traffic.
- Protection of management sessions occurs using RADIUS, TACACS+, and local database authentication as well as secure management sessions over SSL, SSH, and SNMPv3.
- DoS attack prevention maximizes network uptime in the presence of an attack.

## IPv6 Support

As the IP address scheme evolves to accommodate a growing number of network devices, the Cisco 350X Series can support the transition to the next generation of networking and operating systems such as Windows 7, Vista, and Linux. These switches continue to support previous-generation IPv4, allowing you to evolve to the new IPv6 standard at your own pace, and helping ensure that your current network will continue to support your business applications in the future. Cisco 350X Series switches have successfully completed rigorous IPv6 testing and have received the USGv6 and IPv6 Gold certification.

## Advanced Layer 3 Traffic Management

The Cisco 350X Series enables a more advanced set of traffic management capabilities to help growing businesses organize their networks more effectively and efficiently. The switches provide static LAN Layer 3 routing, allowing you to segment your network into workgroups and communicate across VLANs without degrading application performance. With these capabilities, you can boost the efficiency of your network by offloading internal traffic-handling tasks from your router and allowing it to manage primarily external traffic and security. You can minimize the need to manually configure routing devices and simplify the ongoing operation of the network.

## Power Efficiency

The Cisco 350X Series integrates a variety of power-saving features across all models, providing the industry's most extensive energy-efficient switching portfolio. These switches are designed to conserve energy by optimizing power use, which helps protect the environment and reduce your energy costs. They provide an eco-friendly network solution without compromising performance. Cisco 350X Series switches feature:

- 
- Support for the Energy Efficient Ethernet (IEEE 802.3az) standard, which reduces energy consumption by monitoring the amount of traffic on an active link and putting the link into a sleep state during quiet periods
  - The latest application-specific integrated circuits (ASICs), which use low-power 65/40-nanometer technology and low-power, high-performance ARM CPUs
  - Automatic power shutoff on ports when a link is down
  - LEDs that can be turned off to save power
  - Embedded intelligence to adjust signal strength based on the length of the connecting cable

### Networkwide Automatic Voice Deployment

Using a combination of Cisco Discovery Protocol, LLDP-MED, Auto Smartports, and Voice Services Discovery Protocol (or VSDP, a unique Cisco protocol), customers can deploy an end-to-end voice network dynamically. The switches in the network automatically converge around a single voice VLAN and QoS parameters and then propagate them out to the phones on the ports, where they are discovered. For example, automated voice VLAN capabilities let you plug any IP phone (including third-party phones) into your IP telephony network and receive an immediate dial tone. The switch automatically configures the device with the right VLAN and QoS parameters to prioritize voice traffic.

### Peace of Mind and Investment Protection

Cisco 350X Series switches offer the reliable performance and peace of mind you expect from a Cisco switch. When you invest in the Cisco 350 Series, you gain the benefit of:

- Limited lifetime warranty with Next-Business-Day (NBD) advance replacement (where available; otherwise same day ship)
- A solution that has been rigorously tested to help ensure optimal network uptime to keep employees connected to primary resources and productive
- A solution designed and tested to easily and fully integrate with other Cisco voice, unified communications, security, and networking products, as part of a comprehensive technology platform for your business

## Cisco Limited Lifetime Hardware Warranty

Cisco 350X Series switches offer a limited lifetime hardware warranty with NBD advance replacement (where available; otherwise same day ship) and a limited lifetime warranty for fans and power supplies.

In addition, Cisco offers software application updates for bug fixes for the warranty term and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to <https://software.cisco.com/download/navigator.html>.

Product warranty terms and other information applicable to Cisco products are available at <https://www.cisco.com/go/warranty>.

## World-Class Service and Support

Your time is valuable, especially when you have a problem affecting your business. Cisco 350X Series switches are backed by the Cisco SMARTnet<sup>®</sup> Total Care, which provides affordable peace-of-mind coverage. This subscription-based service helps you protect your investment and derive maximum value from Cisco SMB products. Delivered by Cisco and backed by your trusted partner, this comprehensive service includes software updates and access to the Cisco Support Center, and it extends technical service to three years.

Cisco SMB products are supported by professionals in the Cisco Support Center, a dedicated resource for small business customers and networks, with locations worldwide that are specifically trained to understand your needs. You also have access to extensive technical and product information through the Cisco Support Community, an online forum that enables you to collaborate with your peers and reach Cisco technical experts for support information.

## Product Specifications

Table 1 describes product specifications.

Table 1. Specifications

Feature	Description		
Performance			
Switching capacity and forwarding rate  All switches are wire speed and non-blocking	Product Name	Capacity in Mpps (64-Byte Packets)	Switching Capacity (Gbps)
	SG350X-8PMD	29.76	80
	SG350X-24	95.23	128
	SG350X-24P	95.23	128
	SG350X-24MP	95.23	128
	SG350X-24PD	104.16	140
	SG350X-48	130.94	176
	SG350X-48P	130.94	176
	SG350X-48MP	130.94	176
	SG350XG-2F10	178.56	240
	SG350XG-24F	357.12	480
SG350XG-24T	357.12	480	

Feature	Description		
	SG350XG-48T	714.24	960
	SX350X-08	119.05	160
	SX350X-12	178.56	240
	SX350X-24F	357.12	480
	SX350X-24	357.12	480
	SX350X-52	755.81	1040
<b>Layer 2 switching</b>			
<b>Spanning Tree Protocol</b>	Standard 802.1d spanning tree support Fast convergence using 802.1w (Rapid Spanning Tree Protocol [RSTP]), enabled by default Multiple spanning tree instances using 802.1s (MSTP); 8 instances are supported		
<b>Port grouping/link aggregation</b>	Support for IEEE 802.3ad Link Aggregation Control Protocol (LACP) <ul style="list-style-type: none"> <li>• Up to 8 groups</li> <li>• Up to 8 ports per group with 16 candidate ports for each (dynamic) 802.3ad LAG</li> </ul>		
<b>VLAN</b>	Support for up to 4094 active VLANs simultaneously; port-based and 802.1Q tag-based VLANs; MAC-based VLAN Management VLAN Private VLAN with promiscuous, isolated, and community port Guest VLAN, unauthenticated VLAN, protocol-based VLAN, IP subnet-based VLAN, CPE VLAN Dynamic VLAN assignment using RADIUS server along with 802.1x client authentication		
<b>Voice VLAN</b>	Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS. Auto voice capabilities deliver networkwide zero-touch deployment of voice endpoints and call control devices		
<b>Multicast TV VLAN</b>	Multicast TV VLAN allows the single multicast VLAN to be shared in the network while subscribers remain in separate VLANs. This feature is also known as multicast VLAN registration (MVR)		
<b>Q-in-Q</b>	VLANs transparently cross over a service provider network while isolating traffic among customers		
<b>GVRP/GARP</b>	Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP) enable automatic propagation and configuration of VLANs in a bridged domain		
<b>Unidirectional Link Detection (UDLD)</b>	UDLD monitors physical connection to detect unidirectional links caused by incorrect wiring or port faults to prevent forwarding loops and blackholing of traffic in switched networks		
<b>DHCP relay at Layer 2</b>	Relay of DHCP traffic to DHCP server in a different VLAN. Works with DHCP option 82		
<b>IGMP (versions 1, 2, and 3) snooping</b>	Internet Group Management Protocol (IGMP) limits bandwidth-intensive multicast traffic to only the requesters; supports 4K multicast groups (source-specific multicasting is also supported)		
<b>IGMP querier</b>	IGMP querier is used to support a Layer 2 multicast domain of snooping switches in the absence of a multicast router		
<b>HOL blocking</b>	Head-of-line (HOL) blocking		
<b>Layer 3</b>			
<b>IPv4 routing</b>	Wirespeed routing of IPv4 packets Up to 8K static routes and up to 256 IP interfaces		

Feature	Description
Wirespeed IPv6 static routing	Up to 4K static routes and up to 200 IPv6 interfaces
Layer 3 interface	Configuration of Layer 3 interface on physical port, LAG, VLAN interface, or loopback interface
CIDR	Support for classless interdomain routing
DHCP server	Switch functions as an IPv4 DHCP server serving IP addresses for multiple DHCP pools/scopes Support for DHCP options
DHCP relay at Layer 3	Relay of DHCP traffic across IP domains
User Datagram Protocol (UDP) relay	Relay of broadcast information across Layer 3 domains for application discovery or relaying of BOOTP/DHCP packets
<b>Stacking</b>	
Hardware stack	Up to 4 units in a stack. Up to 208 ports managed as a single system with hardware failover
High availability	Fast stack failover delivers minimal traffic loss. Support link aggregation across multiple units in a stack
Plug-and-play stacking configuration/management	Master/backup for resilient stack control Auto-numbering Hot swap of units in stack Ring and chain stacking options, auto-stacking port speed, flexible stacking port options
High-speed stack interconnects	Cost-effective high-speed 10G fiber and copper interfaces. Support LAG as stacking interconnects for even higher bandwidth
<b>Security</b>	
SSH	SSH is a secure replacement for Telnet traffic. SCP also uses SSH. SSH versions 1 and 2 are supported
SSL	Secure Sockets Layer (SSL) encrypts all HTTPS traffic, allowing secure access to the browser-based management GUI in the switch
IEEE 802.1X (authenticator role)	RADIUS authentication and accounting, MD5 hash, guest VLAN, unauthenticated VLAN, single/multiple host mode, and single/multiple sessions Supports time-based 802.1X dynamic VLAN assignment
Web-based authentication	Web-based authentication provides network admission control through web browser to any host devices and operating systems
STP BPDU Guard	A security mechanism to protect the networks from invalid configurations. A port enabled for Bridge Protocol Data Unit (BPDU) Guard is shut down if a BPDU message is received on that port. This avoids accidental topology loops
STP Root Guard	This prevents edge devices not in the network administrator's control from becoming Spanning Tree Protocol root nodes
DHCP snooping	Filters out DHCP messages with unregistered IP addresses and/or from unexpected or untrusted interfaces. This prevents rogue devices from behaving as a DHCP server
IP Source Guard (IPSG)	When IP Source Guard is enabled at a port, the switch filters out IP packets received from the port if the source IP addresses of the packets have not been statically configured or dynamically learned from DHCP snooping. This prevents IP address spoofing

Feature	Description
Dynamic ARP Inspection (DAI)	The switch discards ARP packets from a port if there are no static or dynamic IP/MAC bindings or if there is a discrepancy between the source or destination address in the ARP packet. This prevents man-in-the-middle attacks
IP/MAC/Port Binding (IPMB)	The preceding features (DHCP snooping, IP Source Guard, and Dynamic ARP inspection) work together to prevent DoS attacks in the network, thereby increasing network availability
Secure Core Technology (SCT)	Makes sure that the switch will receive and process management and protocol traffic no matter how much traffic is received
Secure Sensitive Data (SSD)	A mechanism to manage sensitive data (such as passwords, keys, and so on) securely on the switch, populating this data to other devices, and secure autoconfig. Access to view the sensitive data as plaintext or encrypted is provided according to the user-configured access level and the access method of the user
Private VLAN	Private VLAN provides security and isolation between switch ports, which helps ensure that users cannot snoop on other users' traffic; supports multiple uplinks
Port security	Ability to lock source MAC addresses to ports and limit the number of learned MAC addresses
RADIUS/TACACS+	Supports RADIUS and TACACS authentication. Switch functions as a client
RADIUS accounting	The RADIUS accounting functions allow data to be sent at the start and end of services, indicating the amount of resources (such as time, packets, bytes, and so on) used during the session
Storm control	Broadcast, multicast, and unknown unicast
DoS prevention	Denial-of-Service (DoS) attack prevention
Multiple user privilege levels in CLI	Level 1, 7, and 15 privilege levels
ACLs	Support for up to 2K entries Drop or rate limit based on source and destination MAC, VLAN ID or IP address, protocol, port, DSCP/IP precedence, TCP/User Datagram Protocol (UDP) source and destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP) packets, Internet Group Management Protocol (IGMP) packets, TCP flag; ACL can be applied on both ingress and egress sides Time-based ACLs supported

Feature	Description
<b>Quality of service</b>	
Priority levels	8 hardware queues
Scheduling	Strict priority and Weighted Round-Robin (WRR)
Class of service	Port based; 802.1p VLAN priority based; IPv4/v6 IP precedence/ToS/DSCP based; DiffServ; classification and remarking ACLs, trusted QoS Queue assignment based on Differentiated Services Code Point (DSCP) and class of service (802.1p/CoS)
Rate limiting	Ingress policer; egress shaping and ingress rate control; per VLAN, per port, and flow base; 2R3C policing
Congestion avoidance	A TCP congestion avoidance algorithm is required to minimize and prevent global TCP loss synchronization
<b>Standards</b>	
Standards	IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, IEEE 802.3ad Link Aggregation Control Protocol, IEEE 802.3z Gigabit Ethernet, IEEE 802.3ae 10 Gbit/s Ethernet over fiber for LAN, IEEE 802.3an 10GBase-T 10 Gbit/s Ethernet over copper twisted pair cable, IEEE 802.3x Flow Control, IEEE 802.1D (STP, GARP, and GVRP), IEEE 802.1Q/p VLAN, IEEE 802.1w Rapid STP, IEEE 802.1s Multiple STP, IEEE 802.1X Port Access Authentication, IEEE 802.3af, IEEE 802.3at, IEEE 802.1AB Link Layer Discovery Protocol, IEEE 802.3az Energy Efficient Ethernet, RFC 768, RFC 783, RFC 791, RFC 792, RFC 793, RFC 813, RFC 826, RFC 879, RFC 896, RFC 854, RFC 855, RFC 856, RFC 858, RFC 894, RFC 919, RFC 920, RFC 922, RFC 950, RFC 951, RFC 1042, RFC 1071, RFC 1123, RFC 1141, RFC 1155, RFC 1157, RFC 1213, RFC 1215, RFC 1286, RFC 1350, RFC 1442, RFC 1451, RFC 1493, RFC 1533, RFC 1541, RFC 1542, RFC 1573, RFC 1624, RFC 1643, RFC 1700, RFC 1757, RFC 1867, RFC 1907, RFC 2011, RFC 2012, RFC 2013, RFC 2030, RFC 2131, RFC 2132, RFC 2233, RFC 2576, RFC 2616, RFC 2618, RFC 2665, RFC 2666, RFC 2674, RFC 2737, RFC 2819, RFC 2863, RFC 3164, RFC 3176, RFC 3411, RFC 3412, RFC 3413, RFC 3414, RFC 3415, RFC 3416, RFC 4330
<b>IPv6</b>	
IPv6	IPv6 host mode IPv6 over Ethernet dual IPv6/IPv4 stack IPv6 Neighbor and Router Discovery (ND), IPv6 Stateless Address Autoconfiguration, path MTU Discovery Duplicate Address Detection (DAD) ICMPv6 IPv6 over IPv4 network with ISATAP tunnel support USGv6 and IPv6 Gold Logo certified
IPv6 QoS	Prioritize IPv6 packets in hardware
IPv6 ACL	Drop or rate limit IPv6 packets in hardware
IPv6 first hop security	RA guard ND inspection DHCPv6 guard Neighbor binding table (snooping and static entries) Neighbor binding integrity check
Multicast listener discovery (MLD v1/2) snooping	Deliver IPv6 multicast packets only to the required receivers

Feature	Description																																		
IPv6 applications	Web/SSL, Telnet Server/SSH, Ping, Traceroute, SNMP, TFTP, SNMP, RADIUS, Syslog, DNS client, DHCP Client, DHCP Autoconfig, IPv6 DHCP Relay, TACACS																																		
IPv6 RFC supported	<p>RFC 4443 (which obsoletes RFC 2463): ICMPv6</p> <p>RFC 4291 (which obsoletes RFC 3513): IPv6 address architecture</p> <p>RFC 4291: IP Version 6 Addressing Architecture</p> <p>RFC 2460: IPv6 Specification</p> <p>RFC 4861 (which obsoletes RFC 2461): Neighbor Discovery for IPv6</p> <p>RFC 4862 (which obsoletes RFC 2462): IPv6 Stateless Address Autoconfiguration</p> <p>RFC 1981: Path MTU Discovery</p> <p>RFC 4007: IPv6 Scoped Address Architecture</p> <p>RFC 3484: Default address selection mechanism</p> <p>RFC 5214 (which obsoletes RFC 4214): ISATAP tunneling</p> <p>RFC 4293; MIB IPv6: Textual Conventions and General Group</p> <p>RFC 3595; Textual Conventions for IPv6 Flow Label</p>																																		
<b>Management</b>																																			
Web user interface	Built-in switch configuration utility for easy browser-based device configuration (HTTP/HTTPS) Supports simple and advanced mode, configuration, wizards, customizable dashboard, system maintenance, monitoring, online help, and universal search																																		
Smart Network Application	Smart Network Application (SNA) is an innovative network-level monitoring and management tool embedded in Cisco 100 to 500 Series switches. It can discover network topology, display link status, monitor events, apply configurations, and upgrade software images across multiple switches in the network  (Note: Management of your network using Smart Network Application requires the use of either a 250, 350, 350X, or 550X Series switch model as a part of your network)																																		
SNMP	SNMP versions 1, 2c, and 3 with support for traps, and SNMP v3 User-based Security Model (USM)																																		
Standard MIBs	<table border="0"> <tr> <td>lldp-MIB</td> <td>rfc2668-MIB</td> </tr> <tr> <td>lldpextdot1-MIB</td> <td>rfc2737-MIB</td> </tr> <tr> <td>lldpextdot3-MIB</td> <td>rfc2925-MIB</td> </tr> <tr> <td>lldpextmed-MIB</td> <td>rfc3621-MIB</td> </tr> <tr> <td>rfc2674-MIB</td> <td>rfc4668-MIB</td> </tr> <tr> <td>rfc2575-MIB</td> <td>rfc4670-MIB</td> </tr> <tr> <td>rfc2573-MIB</td> <td>trunk-MIB</td> </tr> <tr> <td>rfc2233-MIB</td> <td>tunnel-MIB</td> </tr> <tr> <td>rfc2013-MIB</td> <td>udp-MIB</td> </tr> <tr> <td>rfc2012-MIB</td> <td>draft-ietf-bridge-8021x-MIB</td> </tr> <tr> <td>rfc2011-MIB</td> <td>draft-ietf-bridge-rstp-mib-04-MIB</td> </tr> <tr> <td>RFC-1212</td> <td>draft-ietf-hubmib-etherif-mib-v3-00-MIB</td> </tr> <tr> <td>RFC-1215</td> <td>draft-ietf-syslog-device-MIB</td> </tr> <tr> <td>SNMPv2-CONF</td> <td>ianaaddrfamnumbers-MIB</td> </tr> <tr> <td>SNMPv2-TC</td> <td>ianaifty-MIB</td> </tr> <tr> <td>p-bridge-MIB</td> <td>ianaprot-MIB</td> </tr> <tr> <td>q-bridge-MIB</td> <td>inet-address-MIB</td> </tr> </table>	lldp-MIB	rfc2668-MIB	lldpextdot1-MIB	rfc2737-MIB	lldpextdot3-MIB	rfc2925-MIB	lldpextmed-MIB	rfc3621-MIB	rfc2674-MIB	rfc4668-MIB	rfc2575-MIB	rfc4670-MIB	rfc2573-MIB	trunk-MIB	rfc2233-MIB	tunnel-MIB	rfc2013-MIB	udp-MIB	rfc2012-MIB	draft-ietf-bridge-8021x-MIB	rfc2011-MIB	draft-ietf-bridge-rstp-mib-04-MIB	RFC-1212	draft-ietf-hubmib-etherif-mib-v3-00-MIB	RFC-1215	draft-ietf-syslog-device-MIB	SNMPv2-CONF	ianaaddrfamnumbers-MIB	SNMPv2-TC	ianaifty-MIB	p-bridge-MIB	ianaprot-MIB	q-bridge-MIB	inet-address-MIB
lldp-MIB	rfc2668-MIB																																		
lldpextdot1-MIB	rfc2737-MIB																																		
lldpextdot3-MIB	rfc2925-MIB																																		
lldpextmed-MIB	rfc3621-MIB																																		
rfc2674-MIB	rfc4668-MIB																																		
rfc2575-MIB	rfc4670-MIB																																		
rfc2573-MIB	trunk-MIB																																		
rfc2233-MIB	tunnel-MIB																																		
rfc2013-MIB	udp-MIB																																		
rfc2012-MIB	draft-ietf-bridge-8021x-MIB																																		
rfc2011-MIB	draft-ietf-bridge-rstp-mib-04-MIB																																		
RFC-1212	draft-ietf-hubmib-etherif-mib-v3-00-MIB																																		
RFC-1215	draft-ietf-syslog-device-MIB																																		
SNMPv2-CONF	ianaaddrfamnumbers-MIB																																		
SNMPv2-TC	ianaifty-MIB																																		
p-bridge-MIB	ianaprot-MIB																																		
q-bridge-MIB	inet-address-MIB																																		

Feature	Description	
	rfc1389-MIB rfc1493-MIB rfc1611-MIB rfc1612-MIB rfc1850-MIB rfc1907-MIB rfc2571-MIB rfc2572-MIB rfc2574-MIB rfc2576-MIB rfc2613-MIB rfc2665-MIB	ip-forward-MIB ip-MIB RFC1155-SMI RFC1213-MIB SNMPv2-MIB SNMPv2-SMI SNMPv2-TM RMON-MIB rfc1724-MIB dcb-raj-DCBX-MIB-1108-MIB rfc1213-MIB rfc1757-MIB
<b>Private MIBs</b>	CISCOSB-Ildp-MIB CISCOSB-brgmulticast-MIB CISCOSB-bridgemibobjects-MIB CISCOSB-bonjour-MIB CISCOSB-dhcpcl-MIB CISCOSB-MIB CISCOSB-wrandomtaildrop-MIB CISCOSB-traceroute-MIB CISCOSB-telnet-MIB CISCOSB-stormctrl-MIB CISCOSBssh-MIB CISCOSB-socket-MIB CISCOSB-sntp-MIB CISCOSB-smon-MIB CISCOSB-phy-MIB CISCOSB-multisessionterminal-MIB CISCOSB-mri-MIB CISCOSB-jumboframes-MIB CISCOSB-gvrp-MIB CISCOSB-endofmib-MIB CISCOSB-dot1x-MIB CISCOSB-deviceparams-MIB CISCOSB-cli-MIB CISCOSB-cdb-MIB CISCOSB-brgmacswitch-MIB CISCOSB-3sw2swtables-MIB CISCOSB-smartPorts-MIB CISCOSB-tbi-MIB CISCOSB-macbaseprio-MIB CISCOSB-env_mib-MIB CISCOSB-policy-MIB	CISCOSB-iprouter-MIB CISCOSB-ipv6-MIB CISCOSB-mnginf-MIB CISCOSB-lcli-MIB CISCOSB-localization-MIB CISCOSB-mcmngr-MIB CISCOSB-localization-MIB CISCOSB-mcmngr-MIB CISCOSB-mng-MIB CISCOSB-physdescription-MIB CISCOSB-PoE-MIB CISCOSB-protectedport-MIB CISCOSB-rmon-MIB CISCOSB-rs232-MIB CISCOSB-SecuritySuite-MIB CISCOSB-snmp-MIB CISCOSB-specialbpdu-MIB CISCOSB-banner-MIB CISCOSB-syslog-MIB CISCOSB-TcpSession-MIB CISCOSB-traps-MIB CISCOSB-trunk-MIB CISCOSB-tuning-MIB CISCOSB-tunnel-MIB CISCOSB-udp-MIB CISCOSB-vlan-MIB CISCOSB-ipstdacl-MIB CISCOSB-eee-MIB CISCOSB-ssl-MIB CISCOSB-digitalkeymanage-MIB CISCOSB-qosclimib-MIB

Feature	Description
	CISCOSB-sensor-MIB CISCOSB-aaa-MIB CISCOSB-application-MIB CISCOSB-bridgesecurity-MIB CISCOSB-copy-MIB CISCOSB-CpuCounters-MIB CISCOSB-Custom1BonjourService-MIB CISCOSB-dhcp-MIB CISCOSB-dif-MIB CISCOSB-dnscl-MIB CISCOSB-embweb-MIB CISCOSB-fft-MIB CISCOSB-file-MIB CISCOSB-greeneth-MIB CISCOSB-interfaces-MIB CISCOSB-interfaces_recovery-MIB CISCOSB-ip-MIB CISCOSB-iprouter-MIB CISCOSB-ipv6-MIB CISCOSB-mnginf-MIB CISCOSB-lcli-MIB
	CISCOSB-tbp-MIB CISCOSB-stack-MIB CISCOSMB-MIB CISCOSB-secsd-MIB CISCOSB-draft-ietf-entmib-sensor-MIB CISCOSB-draft-ietf-syslog-device-MIB CISCOSB-rfc2925-MIB CISCO-SMI-MIB CISCOSB-DebugCapabilities-MIB CISCOSB-CDP-MIB CISCOSB-vlanVoice-MIB CISCOSB-EVENTS-MIB CISCOSB-sysmng-MIB CISCOSB-sct-MIB CISCO-TC-MIB CISCO-VTP-MIB CISCO-CDP-MIB
<b>RMON</b>	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis
<b>IPv4 and IPv6 dual stack</b>	Coexistence of both protocol stacks to ease migration
<b>Firmware upgrade</b>	<ul style="list-style-type: none"> <li>• Web browser upgrade (HTTP/HTTPS) and TFTP and SCP</li> <li>• Upgrade can be initiated through console port as well</li> <li>• Dual images for resilient firmware upgrades</li> </ul>
<b>Port mirroring</b>	Traffic on a port or LAG can be mirrored to another port for analysis with a network analyzer or RMON probe. Up to 8 source ports can be mirrored to one destination port
<b>VLAN mirroring</b>	Traffic from a VLAN can be mirrored to a port for analysis with a network analyzer or RMON probe. Up to 8 source VLANs can be mirrored to one destination port
<b>Flow-based redirection and mirroring</b>	Redirect or mirror traffic to a destination port or mirroring session based on flow
<b>Remote Switch Port Analyzer (RSPAN)</b>	Traffic can be mirrored across Layer 2 domain to a remote port on a different switch for easier troubleshooting
<b>sFlow agent</b>	Switch can export sFlow sample to external collectors. sFlow provides visibility into network traffic down to flow level
<b>DHCP (options 12, 66, 67, 82, 129, and 150)</b>	DHCP options facilitate tighter control from a central point (DHCP server), to obtain IP address, auto-configuration (with configuration file download), DHCP Relay, and host name
<b>Auto-configuration with secure</b>	Enables secure mass deployment with protection of sensitive data

Feature	Description
copy (SCP) file download	
Text-editable configs	Config files can be edited with a text editor and downloaded to another switch, facilitating easier mass deployment
Smartports	Simplified configuration of QoS and security capabilities
Auto Smartports	Automatically applies the intelligence delivered through the Smartports roles to the port based on the devices discovered over Cisco Discovery Protocol or LLDP-MED. This facilitates zero-touch deployments
Secure copy (SCP)	Securely transfer files to and from the switch
Textview CLI	Scriptable CLI. A full CLI as well as a menu CLI are supported
Cloud services	Support for Cisco Active Advisor
Localization	Localization of GUI and documentation into multiple languages
Login banner	Configurable multiple banners for web as well as CLI
Time-based port operation	Link up or down based on user-defined schedule (when the port is administratively up)
Other management	Traceroute; single IP management; HTTP/HTTPS; SSH; RADIUS; port mirroring; TFTP upgrade; DHCP client; Simple Network Time Protocol (SNTP); Xmodem upgrade; cable diagnostics; Ping; syslog; Telnet client; SSH client; automatic time settings from Management Station
<b>Green (power efficiency)</b>	
Energy detect	Automatically turns power off on RJ-45 port when detecting link down. Active mode is resumed without loss of any packets when the switch detects the link is up
Cable length detection	Adjusts the signal strength based on the cable length. Reduces the power consumption for shorter cables
EEE compliant (802.3az)	Supports IEEE 802.3az on all 10 Gigabit copper ports
Disable port LEDs	LEDs can be manually turned off to save on energy
<b>General</b>	
Jumbo frames	Frame sizes up to 9K bytes. The default MTU is 2K
MAC table	16K addresses

Feature	Description				
<b>Discovery</b>					
Bonjour	The switch advertises itself using the Bonjour protocol				
LLDP (802.1ab) with LLDP-MED extensions	Link Layer Discovery Protocol (LLDP) allows the switch to advertise its identification, configuration, and capabilities to neighboring devices that store the data in a MIB. LLDP-MED is an enhancement to LLDP that adds the extensions needed for IP phones				
Cisco Discovery Protocol	The switch advertises itself using the Cisco Discovery Protocol. It also learns the connected device and its characteristics using Cisco Discovery Protocol				
<b>Product specifications</b>					
Power over Ethernet	The following switches support 802.3at PoE+, 802.3af PoE, and Cisco pre-standard (legacy) PoE on any of the RJ45 network ports. 60W PoE is also supported on selected RJ-45 network ports Maximum power of 60W is delivered to any of the 60W PoE ports, and maximum power of 30W is delivered to any of the other RJ45 network ports, until the PoE budget for the switch is reached The total power available for PoE per switch is as follows				
	<b>Model</b>	<b>Power Dedicated to PoE</b>	<b>Number of Ports That Support PoE</b>		
	SG350X-8PMD	240W	8 (4 support 60W PoE)		
	SG350X-24P	195W	24 (4 support 60W PoE)		
	SG350X-24MP	382W	24 (4 support 60W PoE)		
	SG350X-24PD	375W	24 (4 support 60W PoE)		
	SG350X-48P	382W	48 (8 support 60W PoE)		
	SG350X-48MP	740W	24 (8 support 60W PoE)		
Power consumption (worst case)	<b>Model Name</b>	<b>Green Power (Mode)</b>	<b>System Power Consumption</b>	<b>Power Consumption (with PoE)</b>	<b>Heat Dissipation (BTU/hr)</b>
	SG350X-8PMD	EEE, Energy Detect, Short Reach	110V=32.5W 220V=32.5W	N/A	1065.3
	SG350X-24	EEE, Energy Detect, Short Reach	110V=32.5W 220V=32.5W	N/A	83.39
	SG350X-24P	EEE, Energy Detect, Short Reach	110V=48.8W 220V=49.3W	110V=269.2W 220V=260.1W	764.18
	SG350X-24MP	EEE, Energy Detect, Short Reach	110V=53.8W 220V=54.8W	110V=471.2W 220V=460.4W	1,607.80
	SG350X-24PD	EEE, Energy Detect, Short Reach	110V=48.8W 220V=49.3W	110V=269.2W 220V=260.1W	1625.3
	SG350X-48	EEE, Energy Detect, Short Reach	110V=52.0W 220V=51.8W	N/A	177.43
	SG350X-48P	EEE, Energy Detect, Short Reach	110V=76.3W 220V=76.9W	110V=494.3W 220V=483.1W	1,686.62

Feature	Description				
	SG350X-48MP	EEE, Energy Detect, Short Reach	110V=82.9W 220V=82.9W	110V=893.1W 220V=878.0W	3,047.38
	SG350XG-2F10	EEE, Energy Detect, Short Reach	110V=84.3W 220V=84.6W	N/A	288.67
	SG350XG-24F	EEE, Energy Detect, Short Reach	110V=76.6W 220V=77.5W	N/A	264.44
	SG350XG-24T	EEE, Energy Detect, Short Reach	110V=143.9W 220V=142.9W	N/A	491.01
	SG350XG-48T	EEE, Energy Detect, Short Reach	110V=264.4W 220V=255.8W	N/A	902.17
	SX350X-08	EEE, Energy Detect, Short Reach	110V=50.3W 220V=50.3W	N/A	171.63
	SX350X-12	EEE, Energy Detect, Short Reach	110V=63.9W 220V=64.1W	N/A	202.27
	SX350X-24F	EEE, Energy Detect, Short Reach	110V=38.5W 220V=39.0W	N/A	133.07
	SX350X-24	EEE, Energy Detect, Short Reach	110V=121.1W 220V=124.5W	N/A	404.13
	SX350XG-52	EEE, Energy Detect, Short Reach	110V=234.4W 220V=229.2W	N/A	917.18
<b>Ports</b>	<b>Model Name</b>	<b>Total System Ports</b>	<b>Network Ports</b>	<b>Uplink Ports</b>	
	SG350X-8PMD	8 2.5GE + 2 10GE	8 2.5GE	2 10GE copper/SFP+ combo	
	SG350X-24	24 GE + 4 10GE	24 GE	2 10GE copper/SFP+ combo + 2 SFP+	
	SG350X-24P	24 GE + 4 10GE	24 GE	2 10GE copper/SFP+ combo + 2 SFP+	

Feature	Description			
	SG350X-24MP	24 GE + 4 10GE	24 GE	2 10GE copper/SFP+ combo + 2 SFP+
	SG350X-24PD	20 GE + 4 1G/2.5GE + 4 10GE	20 GE + 4 1G/2.5G	2 10GE copper/SFP+ combo + 2 SFP+
	SG350X-48	48 GE + 4 10GE	48 GE	2 10GE copper/SFP+ combo + 2 SFP+
	SG350X-48P	48 GE + 4 10GE	48 GE	2 10GE copper/SFP+ combo + 2 SFP+
	SG350X-48MP	48 GE + 4 10GE	48 GE	2 10GE copper/SFP+ combo + 2 SFP+
	SG350XG-2F10	10 10G copper + 2 10G SFP+ plus 1 GE OOB management	10 10GE	2 10GE SFP+ (dedicated)
	SG350XG-24F	22 10G SFP+ slots + 2 combo 10G copper/SFP+ plus 1 GE OOB management	22 10GE SFP+	2 10GE copper/SFP+ combo
	SG350XG-24T	22 10G copper + 2 combo 10G copper/SFP+ plus 1 GE OOB management	22 10GE	2 10GE copper/SFP+ combo
	SG350XG-48T	46 10G copper + 2 combo 10G copper/SFP+ plus 1 GE OOB management	46 10GE	2 10GE copper/SFP+ combo
	SX350X-08	6 10G copper + 2 10G SFP+ plus 1 GE OOB management	6 10GE	2 10GE Copper/SFP+ Combo
	SX350X-12	10 10G copper + 2 10G SFP+ plus 1 GE OOB management	10 10GE	2 10GE Copper/SFP+ Combo
	SX350X-24F	20 10G SFP+ slots + 4 combo 10G copper/SFP+ plus 1 GE OOB management	20 10GE SFP+	4 10GE Copper/SFP+ Combo

Feature	Description			
	SX350X-24	20 10G copper + 4 combo 10G copper/SFP+ plus 1 GE OOB management	20 10GE	4 10GE Copper/SFP+ Combo
	SX350X-52	48 10G copper + 4 combo 10G copper/SFP+ plus 1 GE OOB management	48 10GE	4 10GE Copper/SFP+ Combo
<b>Console port</b>	Cisco Standard RJ45 console port			
<b>OOB management port</b>	Dedicated Gigabit management port for out-of-band management on SG350XG models			
<b>USB slot</b>	USB Type-A slot on the front panel of the switch for easy file and image management			
<b>Buttons</b>	Reset button			
<b>Cabling type</b>	Unshielded Twisted Pair (UTP) Category 5 or better; fiber options (SMF and MMF); coaxial SFP+			
<b>LEDs</b>	System, master, stack ID, link/speed per port			
<b>Flash</b>	256 MB			
<b>CPU</b>	800 MHz (dual-core) ARM			
<b>CPU memory</b>	512 MB			
<b>Packet buffer</b>	All numbers are aggregate across all ports because the buffers are dynamically shared:			
	<b>Model Name</b>	<b>Packet Buffer</b>		
	SG350X-8PMD	12 MB		
	SG350X-24	1.5 MB		
	SG350X-24P	1.5 MB		
	SG350X-24MP	1.5 MB		
	SG350X-24PD	24 MB		
	SG350X-48	3 MB		
	SG350X-48P	3 MB		
	SG350X-48MP	3 MB		
	SG350XG-2F10	2 MB		
	SG350XG-24F	2 MB		
	SG350XG-24T	2 MB		
	SG350XG-48T	4 MB		
	SX350X-08	3MB		
	SX350X-12	3MB		

Feature	Description		
	SX350X-24F	3MB	
	SX350X-24	3MB	
	SX350X-52	10MB	
<b>Environmental</b>			
<b>Unit dimensions (W x H x D)</b>	<b>Model Name</b>	<b>Unit Dimensions</b>	
	SG350X-8PMD	344.4 x 44 x 252.5 mm (13.6 x 1.45 x 9.94 in)	
	SG350X-24	440 x 44 x 257 mm (17.3 x 1.45 x 10.12 in)	
	SG350X-24P	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SG350X-24MP	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SG350X-24PD	440 x 44 x 257 mm (17.3 x 1.45 x 10.12 in)	
	SG350X-48	440 x 44 x 257 mm (17.3 x 1.45 x 10.12 in)	
	SG350X-48P	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SG350X-48MP	440 x 44 x 450 mm (17.3 x 1.45 x 17.72 in)	
	SG350XG-2F10	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SG350XG-24F	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SG350XG-24T	440 x 44 x 450 mm (17.3 x 1.45 x 17.72 in)	
	SG350XG-48T	440 x 44 x 450 mm (17.3 x 1.45 x 17.72 in)	
	SX350X-08	440 x 44 x 203 mm (17.3 x 1.6 x 8.0 in)	
	SX350X-12	440 x 44 x 203 mm (17.3 x 1.6 x 8.0 in)	
	SX350X-24F	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SX350X-24	440 x 44 x 350 mm (17.3 x 1.45 x 13.78 in)	
	SX350X-52	440 x 44 x 450 mm (17.3 x 1.45 x 17.72 in)	
	<b>Unit weight</b>	<b>Model Name</b>	<b>Unit Weight</b>
		SG350X-8PMD	2.74 kg (6.04 lb)
SG350X-24		4.32 kg (9.52 lb)	
SG350X-24P		4.93 kg (10.41 lb)	
SG350X-24MP		5.69 kg (11.75 lb)	
SG350X-24PD		3.99 kg (8.79 lb)	
SG350X-48		3.73 kg (8.22 lb)	
SG350X-48P		5.82 kg (12.83 lb)	

Feature	Description			
	SG350X-48MP		6.69 kg (14.75 lb)	
	SG350XG-2F10		4.03 kg (8.88 lb)	
	SG350XG-24F		4.16 kg (9.17 lb)	
	SG350XG-24T		5.57 kg (12.28 lb)	
	SG350XG-48T		7.43 kg (16.38 lb)	
	SX350X-08		2.98 kg (6.57 lb)	
	SX350X-12		2.93 kg (6.46 lb)	
	SX350X-24F		4.4 kg (9.7 lb)	
	SX350X-24		5.1 (11.2 lb)	
	SX350X-52		7.29. (16.1 lb)	
<b>Power</b>	100 - 240V 47 - 63 Hz, internal, universal			
<b>Certification</b>	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A			
<b>Operating temperature</b>	SG350XG-2F10, SG350XG-24F, SG350XG-24T, SG350XG-48T, SX350X-08, SX350X-12, SX350X-24F, SX350X-24, SG350XG-52 32° to 122°F (0° to 50°C)			
<b>Storage temperature</b>	-4° to 158°F (-20° to 70°C)			
<b>Operating humidity</b>	10% to 90%, relative, noncondensing			
<b>Storage humidity</b>	10% to 90%, relative, noncondensing			
<b>Acoustic noise and Mean Time Between Failures (MTBF)</b>	<b>Model Name</b>	<b>Fan (Number)</b>	<b>Acoustic Noise</b>	<b>MTBF at 50°C (Hours)</b>
	SG350X-8PMD	1	42.9 at 45°C	474,265
	SG350X-24	1	0°C - 30°C: 36.3dB 50°C: 49.3dB	385,289
	SG350X-24P	2	0°C - 30°C: 41.0dB 50°C: 52.9dB	244,654
	SG350X-24MP	2	0°C - 30°C: 43.3dB 50°C: 52.3dB	144,617
	SG350X-24PD	3	45.1 at 45°C	426,741
	SG350X-48	1	0°C - 30°C: 35.0dB 50°C: 51.7dB	248,842
	SG350X-48P	3	0°C - 30°C: 43.8dB 50°C: 52.1dB	164,614
	SG350X-48MP	4	0°C - 30°C: 43.2dB 50°C: 53.2dB	171,530

Feature	Description			
	SG350XG-2F10	3	0°C - 30°C: 38.9dB 50°C: 49.7dB	291,863
	SG350XG-24F	4	0°C - 25°C: 36.4dB	194,544
	SG350XG-24T	4	0°C-30°C: 40.7dB 50°C: 51.7dB	347,052
	SG350XG-48T	4	0°C-30°C: 47.7dB 50°C: 58.9dB	131,767
	SX350X-08	3	0°C - 30°C: 38.9dB 50°C: 49.7dB	1,418,411
	SX350X-12	3	0°C - 30°C: 38.9dB 50°C: 49.7dB	633,325
	SX350X-24F	4	0°C - 25°C: 36.4dB	1,356,179
	SX350X-24	4	0°C-30°C: 40.7dB 50°C: 51.7dB	556,643
	SX350X-52	4	0°C-30°C: 47.7dB 50°C: 58.9dB	287,136
<b>Warranty</b>	Limited lifetime with next-business-day advance replacement (where available, otherwise same day ship)			

### Package Contents

- Cisco Small Business 350X Series Stackable Managed Switch
- Power cord
- Mounting kit included with all models
- Console cable
- Quick Start Guide

### Minimum Requirements

- Web browser: Mozilla Firefox version 8 or later; Microsoft Internet Explorer version 7 or later, Safari, Chrome
- Category 6a Ethernet network cable for 10 Gig speeds at up to 100m
- TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed

## Ordering Information

Table 2 provides ordering information.

**Table 2.** Ordering Information

Model Name	Product Order ID Number	Description
SG350X-8PMD	SG350X-8PMD-K9	<ul style="list-style-type: none"> <li>• 8 x 100FE/1G/2.5G ports</li> <li>• 2 x 10GBase-T/SFP+ combo</li> <li>• 240W power budget, 8 PoE ports (4 support 60W PoE)</li> </ul>
SG350X-24	SG350X-24-K9	<ul style="list-style-type: none"> <li>• 24 x 10/100/1000 ports</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> </ul>
SG350X-24P	SG350X-24P-K9	<ul style="list-style-type: none"> <li>• 24 x 10/100/1000 PoE+ ports</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> <li>• 195W power budget, 24 PoE ports (4 support 60W PoE)</li> </ul>
SG350X-24MP	SG350X-24MP-K9	<ul style="list-style-type: none"> <li>• 24 x 10/100/1000</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> <li>• 382W power budget, 24 PoE ports (4 support 60W PoE)</li> </ul>
SG350X-24PD	SG350X24PD-K9	<ul style="list-style-type: none"> <li>• 20 x 10/100/1000</li> <li>• 4 x 100FE/1G/2.5G PoE+ ports</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> <li>• 375W power budget, 24 PoE ports (4 support 60W PoE)</li> </ul>
SG350X-48	SG350X-48-K9	<ul style="list-style-type: none"> <li>• 48 x 10/100/1000 ports</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> </ul>
SG350X-48P	SG350X-48P-K9	<ul style="list-style-type: none"> <li>• 48 x 10/100/1000</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> <li>• 382W power budget, 48 PoE ports (8 support 60W PoE)</li> </ul>
SG350X-48MP	SG350X-48MP-K9	<ul style="list-style-type: none"> <li>• 48 x 10/100/1000</li> <li>• 4 x 10 Gigabit Ethernet (2 x 10GBase-T/SFP+ combo + 2 x SFP+)</li> <li>• 740W power budget, 48 PoE ports (8 support 60W PoE)</li> </ul>
SG350XG-2F10	SG350XG-2F10-K9	<ul style="list-style-type: none"> <li>• 10 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 2 x 10 Gigabit Ethernet SFP+ (dedicated)</li> </ul>
SG350XG-24F	SG350XG-24F-K9	<ul style="list-style-type: none"> <li>• 22 x 10 Gigabit Ethernet SFP+</li> <li>• 2 x 10 Gigabit Ethernet 10Gbase-T copper port (combo with 2 SFP+)</li> </ul>
SG350XG-24T	SG350XG-24T-K9	<ul style="list-style-type: none"> <li>• 22 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 2 x 10 Gigabit Ethernet SFP+ (combo with 2 copper ports)</li> </ul>
SG350XG-48T	SG350XG-48T-K9	<ul style="list-style-type: none"> <li>• 46 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 2 x 10 Gigabit Ethernet SFP+ (combo with 2 copper ports)</li> </ul>
SX350X-08	SX350X-08-K9	<ul style="list-style-type: none"> <li>• 6 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 2 x 10 Gigabit Ethernet SFP+ (combo with 2 copper ports)</li> </ul>
SX350X-12	SX350X-12-K9	<ul style="list-style-type: none"> <li>• 10 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 2 x 10 Gigabit Ethernet SFP+ (combo with 2 copper ports)</li> </ul>

Model Name	Product Order ID Number	Description
SX350X-24F	SX350X-24F-K9	<ul style="list-style-type: none"> <li>• 20 x 10 Gigabit Ethernet SFP+</li> <li>• 4 x 10 Gigabit Ethernet 10GBase-T copper port (combo with 4 SFP+)</li> </ul>
SX350X-24	SX350X-24-K9	<ul style="list-style-type: none"> <li>• 20 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 4 x 10 Gigabit Ethernet SFP+ (combo with 4 copper ports)</li> </ul>
SX350X-52	SX350X-52-K9	<ul style="list-style-type: none"> <li>• 48 x 10 Gigabit Ethernet 10GBase-T copper port</li> <li>• 4 x 10 Gigabit Ethernet SFP+ (combo with 4 copper ports)</li> </ul>

\*Each combo port has one 10/100/1000/10000 copper Ethernet port and one SFP+ Gigabit Ethernet slot, with one port active at a time.

The -xx in the Product Order ID Number is a country-/region-specific suffix. For example, the complete PID of SG350-28P for the United States is SG350-28P-K9-NA. Please refer to Table 2 for the correct suffix to use for your country/region.

**Table 3.** Country/Region Suffix for Product Order ID Number

Suffix	Country/Region
-NA	<ul style="list-style-type: none"> <li>• USA, Canada, Mexico, Colombia, Chile and rest of LATAM</li> </ul>
-BR	<ul style="list-style-type: none"> <li>• Brazil</li> </ul>
-AR	<ul style="list-style-type: none"> <li>• Argentina</li> </ul>
-EU	<ul style="list-style-type: none"> <li>• EU, Russia, Ukraine, Israel, UAE, Turkey, Egypt, South Africa, Indonesia, Philippines, Vietnam, Thailand, India, Korea</li> </ul>
-UK	<ul style="list-style-type: none"> <li>• United Kingdom, Saudi Arabia, Qatar, Kuwait, Singapore, Hong Kong, Malaysia</li> </ul>
-AU	<ul style="list-style-type: none"> <li>• Australia, New Zealand</li> </ul>
-CN	<ul style="list-style-type: none"> <li>• China</li> </ul>
-IN	<ul style="list-style-type: none"> <li>• India</li> </ul>
-JP	<ul style="list-style-type: none"> <li>• Japan</li> </ul>
-KR	<ul style="list-style-type: none"> <li>• Korea</li> </ul>

The products may also be available in a country/region not listed in Table 3. Not all product models are offered in all countries/regions. For India, either -EU or -IN suffix will be used depending on product models. For Korea, either -EU or -KR suffix will be used depending on product models. Please consult with your local Cisco sales representative or Cisco partners for more details.

### An Advanced Technology Backbone for Growing Businesses

Growth is never a bad thing. But as you gain new customers and a higher profile, you need a business technology platform capable of delivering a higher level of service and reliability. With more users, more devices and applications, and more exposure to security threats, a switching platform designed for a smaller operation simply cannot meet your growing needs. It's time for a network that will support your business as you take it to the next level. Cisco 350X Series switches provide the advanced feature set, reliability, and investment protection your business needs, today and in the future.

---

## Cisco Capital

### Flexible Payment Solutions to Help You Achieve Your Objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

### For More Information

To find out more about the Cisco 350X Series, visit <https://www.cisco.com/go/350Xswitches>.

To learn about other products and solutions in the Cisco Small Business portfolio, visit <https://www.cisco.com/go/smallbusiness>.

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)